



# INSTRUCTION MANUAL

HF/50 MHz  
ALL MODE TRANSCEIVER  
**IC-756PRO**



---

## IMPORTANT

---

**READ THIS INSTRUCTION MANUAL CAREFULLY** before attempting to operate the transceiver.

**SAVE THIS INSTRUCTION MANUAL.** This manual contains important safety and operating instructions for the IC-756PRO.

---

## PRECAUTIONS

---

⚠ **WARNING HIGH VOLTAGE! NEVER** attach an antenna or internal antenna connector during transmission. This may result in an electrical shock or burn.

⚠ **NEVER** apply AC to the [DC13.8V] jack on the transceiver rear panel. This could cause a fire or ruin the transceiver.

⚠ **NEVER** apply more than 16 V DC, such as a 24 V battery, to the [DC13.8V] jack on the transceiver rear panel. This could cause a fire or ruin the transceiver.

⚠ **NEVER** let metal, wire or other objects touch any internal part or connectors on the rear panel of the transceiver. This may result in an electric shock.

**NEVER** expose the transceiver to rain, snow or any liquids.

**AVOID** using or placing the transceiver in areas with temperatures below  $-10^{\circ}\text{C}$  ( $+14^{\circ}\text{F}$ ) or above  $+60^{\circ}\text{C}$  ( $+140^{\circ}\text{F}$ ). Be aware that temperatures on a vehicle's dashboard can exceed  $80^{\circ}\text{C}$  ( $+176^{\circ}\text{F}$ ), resulting in permanent damage to the transceiver if left there for extended periods.

**AVOID** placing the transceiver in excessively dusty environments or in direct sunlight.

**AVOID** placing the transceiver against walls or putting anything on top of the transceiver. This will obstruct heat dissipation.

---

## EXPLICIT DEFINITIONS

---

WORD	DEFINITION
⚠ <b>WARNING</b>	Personal injury, fire hazard or electric shock may occur.
<b>CAUTION</b>	Equipment damage may occur.
<b>NOTE</b>	If disregarded, inconvenience only. No risk of personal injury, fire or electric shock.

Place unit in a secure place to avoid inadvertent use by children.

During mobile operation, **DO NOT** operate the transceiver without running the vehicle's engine. When transceiver power is ON and your vehicle's engine is OFF, the vehicle's battery will soon become exhausted.

Make sure the transceiver power is OFF before starting the vehicle. This will avoid possible damage to the transceiver by ignition voltage spikes.

During maritime mobile operation, keep the transceiver and microphone as far away as possible from the magnetic navigation compass to prevent erroneous indications.

**BE CAREFUL!** The heatsink will become hot when operating the transceiver continuously for long periods.

**BE CAREFUL!** If a linear amplifier is connected, set the transceiver's RF output power to less than the linear amplifier's maximum input level, otherwise, the linear amplifier will be damaged.

Use Icom microphones only (supplied or optional). Other manufacturer's microphones have different pin assignments, and connection to the IC-756PRO may damage the transceiver.

Spurious may be received near the following frequencies. These are made in the internal circuit and does not indicate a transceiver malfunction:

6.144 MHz, 8.000 MHz,  
12.288 MHz, 12.890 MHz (when spectrum scope is ON),  
18.433 MHz, 24.573 MHz




Versions of the IC-756PRO which display the "CE" symbol on the serial number seal, comply with the European harmonised standard ETS300 684 (EMC product standard for Commercially Available Amateur Radio Equipment).

<b>IMPORTANT</b> .....	i	<b>5 RECEIVE AND TRANSMIT</b> ..	26–49	■ $\Delta$ F scan operation .....	57
<b>EXPLICIT DEFINITIONS</b> .....	i	■ Mode selection .....	26	■ Fine programmed scan/ fine $\Delta$ F scan .....	58
<b>PRECAUTIONS</b> .....	i	■ Twin PBT operation .....	26	■ Memory scan operation .....	58
<b>1 TABLE OF CONTENTS</b> .....	1	■ Notch function .....	27	■ Select memory scan operation .....	59
<b>2 PANEL DESCRIPTION</b> .....	2–13	■ Noise reduction .....	27	■ Setting select memory channels ..	59
■ Front panel .....	2	■ Noise blanker .....	27	■ Scan set mode .....	60
■ Microphone (HM-36) .....	9	■ RTTY filter/Twin peak filter .....	28	■ Tone scan .....	61
■ LCD display .....	10	■ CW reverse mode .....	28	<b>8 CLOCK AND TIMERS</b> .....	62–63
■ Screen menu arrangement .....	11	■ RTTY reverse mode .....	28	■ Setting the current time .....	62
■ Rear panel .....	12	■ CW pitch control .....	29	■ Setting power-on time .....	62
<b>3 INSTALLATION AND</b>		■ IF filter selection .....	29	■ Setting power-off period .....	63
<b>CONNECTIONS</b> .....	14–21	■ AGC function .....	30	■ Timer operation .....	63
■ Unpacking .....	14	■ Dualwatch operation .....	31	<b>9 SET MODE</b> .....	64–72
■ Selecting a location .....	14	■ Split frequency operation .....	32	■ Set mode description .....	64
■ Grounding .....	14	■ Quick split function .....	33	■ Level set mode .....	65
■ Antenna connection .....	14	■ RIT and $\Delta$ TX .....	34	■ Display set mode .....	66
■ Required connections .....	15	■ Monitor function .....	35	■ Timer set mode .....	67
■ Advanced connections .....	16	■ VOX function .....	35	■ Miscellaneous (others) set mode ..	68
■ Power supply connections .....	17	■ Meter function .....	36	<b>10 OPTION INSTALLATION</b> .....	73
■ Linear amplifier connections .....	18	■ SWR reading .....	36	■ Opening the transceiver's case ....	73
■ Transverter jack information .....	19	■ Speech compressor .....	37	■ UT-102 VOICE SYNTHESIZER	
■ External antenna selector or		■ Digital voice recorder .....	38	UNIT .....	73
antenna tuner connections .....	20	■ RTTY decoder .....	41	<b>11 MAINTENANCE</b> .....	74–76
■ FSK and AFSK (SSTV)		■ RTTY tuning meter .....	41	■ Troubleshooting .....	74
connections .....	21	■ Electronic CW keyer .....	42	■ Fuse replacement .....	75
<b>4 FREQUENCY SETTING</b> .....	22–25	■ Memory keyer .....	43	■ Clock backup battery	
■ When first applying power		■ Spectrum scope screen .....	44	replacement .....	75
(CPU resetting) .....	22	■ Automatic antenna selection .....	45	■ Tuning dial brake adjustment .....	76
■ Initial settings .....	22	■ Dial lock function .....	45	■ Frequency calibration	
■ VFO description .....	23	■ Repeater operation .....	46	(approximate) .....	76
■ Frequency setting with the		■ Tone squelch operation .....	47	<b>12 INTERNAL VIEWS</b> .....	77
tuning dial .....	24	■ Antenna tuner operation .....	48	<b>13 CONTROL COMMAND</b> .....	78–79
■ Direct frequency entry with		■ Optional external tuner		■ Remote jack (CI-V) information ....	78
the keypad .....	24	operation .....	49	<b>14 SPECIFICATIONS</b> .....	80
■ Advanced tuning functions .....	25	<b>6 MEMORY OPERATION</b> .....	50–55	<b>15 OPTIONS</b> .....	81
<b>5 RECEIVE AND TRANSMIT</b> ..	26–49	■ Memory channels .....	50		
■ Mode selection .....	26	■ Memory channel selection .....	50		
■ Twin PBT operation .....	26	■ Memory channel screen .....	51		
■ Notch function .....	27	■ Memory channel programming .....	52		
■ Noise reduction .....	27	■ Frequency transferring .....	53		
■ Noise blanker .....	27	■ Memory names .....	54		
■ RTTY filter/Twin peak filter .....	28	■ Memory clearing .....	54		
■ CW reverse mode .....	28	■ Memo pads .....	55		
■ RTTY reverse mode .....	28	<b>7 SCANS</b> .....	56–61		
■ CW pitch control .....	29	■ Scan types .....	56		
■ IF filter selection .....	29	■ Preparation .....	56		
■ AGC function .....	30	■ Programmed scan operation .....	57		
■ Dualwatch operation .....	31				
■ Split frequency operation .....	32				
■ Quick split function .....	33				
■ RIT and $\Delta$ TX .....	34				
■ Monitor function .....	35				
■ VOX function .....	35				
■ Meter function .....	36				
■ SWR reading .....	36				
■ Speech compressor .....	37				
■ Digital voice recorder .....	38				
■ RTTY decoder .....	41				
■ RTTY tuning meter .....	41				
■ Electronic CW keyer .....	42				
■ Memory keyer .....	43				
■ Spectrum scope screen .....	44				
■ Automatic antenna selection .....	45				
■ Dial lock function .....	45				
■ Repeater operation .....	46				
■ Tone squelch operation .....	47				
■ Antenna tuner operation .....	48				
■ Optional external tuner					
operation .....	49				


## SUPPLIED ACCESSORIES

The transceiver comes with the following accessories.

	<b>Qty.</b>
① DC power cable (OPC-025D) .....	1
② Hand microphone (HM-36) .....	1
③ Spare fuses (FGB 30 A) .....	2
④ Spare fuse (FGB 5 A) .....	1
⑤ CW keyer plug (AP-330) .....	1



## ■ Front panel



### 1 POWER SWITCH [POWER/TIMER]

- ➔ Push momentarily to turn power ON.
  - Turn the optional DC power supply ON in advance.
  - A/D converter calibration of the DSP unit starts and it takes 10 sec.
- ➔ Push momentarily to toggle the timer function ON and OFF. (p. 63)
  - The power switch lights while the timer function is ON.
- ➔ Push for 2 sec. to turn power OFF.

### 2 TRANSMIT SWITCH [TRANSMIT]


- Selects transmitting or receiving.
- The [TX] indicator lights red while transmitting and the [RX] indicator lights green when the squelch is open.

### 3 HEADPHONE JACK [PHONES]

- Accepts headphones.
- Output power: 5 mW with an 8 Ω load.
  - When headphones are connected, the internal speaker or connected external speaker does not function.

### 4 ELECTRONIC KEYS JACK [ELEC-KEY] (p. 42)

- Accepts a paddle to activate the internal electronic keyer for CW operation.
- Selection between the internal electronic keyer, bug-key and straight key operation can be made in keyer set mode. (p. 42)
  - A straight key jack is separately available on the rear panel. See [KEY] on p. 12.
  - Keyer polarity (dot and dash) can be reversed in keyer set mode. (p. 42)
  - 4-channel memory keyer is available for your convenience. (p. 43)




### 5 MICROPHONE CONNECTOR [MIC]

- Accepts the supplied or optional microphone.
- See p. 81 for appropriate microphones.
  - See p. 9 for microphone connector information.

### 6 AF CONTROL [AF] (inner control)

- Varies the audio output level from the speaker.




### 7 MIC GAIN CONTROL [MIC GAIN]

- Adjusts microphone input gain.
- The transmit audio tone in SSB mode can be adjusted in set mode. (p. 65)

#### ✓ How to set the microphone gain.

Set the [MIC] control so that the ALC meter sometimes swings during normal voice transmission in SSB mode.




**8 RF GAIN CONTROL/SQUELCH CONTROL [RF/SQL] (outer control)**

Adjusts the RF gain and squelch threshold level. The squelch removes noise output from the speaker (closed condition) when no signal is received.


- The squelch is particularly effective for FM. It is also available for other modes.
- 12 to 1 o'clock position is recommended for any setting of the [RF/SQL] control.
- The control can be set as 'Auto' (RF gain control in SSB, CW and RTTY; squelch control in AM and FM) or squelch control (RF gain is fixed at maximum) in set mode as follows. (p. 68)

MODE	SET MODE SETTING		
	AUTO	SQL	RF GAIN + SQL
SSB, CW RTTY	RF GAIN	SQL	RF GAIN + SQL
AM, FM	SQL	SQL	RF GAIN + SQL


**•When setting as RF gain/squelch control**



**•When functioning as RF gain control**  
(Squelch is fixed open; SSB, CW, RTTY only)



**•When functioning as squelch control**  
(RF gain is fixed at maximum.)



While rotating the RF gain control, noise may be heard. This comes from the DSP unit and does not indicate an equipment malfunction.

**9 RF POWER CONTROL [RF POWER]**


Continuously varies the RF output power from minimum (5 W\*) to maximum (100 W\*).

\*AM mode: 5 W to 40 W



**10 BALANCE CONTROL [BAL] (inner control; p. 31)**


Adjusts the audio output balance between main and sub readout frequencies while in dualwatch.



**11 NOISE REDUCTION LEVEL CONTROL [NR]**


(outer control; p. 27)

Adjusts the noise reduction level when the noise reduction is in use. Set for maximum readability.




**12 NOISE REDUCTION SWITCH [NR] (p. 27)**

Toggles the noise reduction ON and OFF.



**13 NOISE BLANKER SWITCH [NB] (p. 27)**

Toggles the noise blanker ON and OFF. The noise blanker reduces pulse-type noise such as that generated by automobile ignition systems. This function cannot be used for FM, or non-pulse-type noise.



**14 S/RF METER (p. 36)**

Shows the signal strength while receiving. Shows the relative output power, SWR, ALC or compression levels while transmitting.

**15 MONITOR SWITCH [MONITOR] (p. 35)**

Monitors your transmitted IF signal.

- The CW sidetone functions when [MONITOR] is OFF in CW mode.


**16 ANTENNA TUNER SWITCH [TUNER] (p. 48)**

Turns the antenna tuner ON and OFF (bypass) when pushed momentarily.

Starts to tune the antenna manually when pushed for 2 sec.

- When the tuner cannot tune the antenna, the tuning circuit is bypassed automatically after 20 sec.

■ Front panel (continued)



**17 COMPRESSION LEVEL CONTROL [COMP]**

(p. 37)

Adjusts the speech compression level in SSB.



**18 ELECTRONIC CW KEYS SPEED CONTROL [KEY SPEED]** (p. 42)

Adjusts the internal electronic CW keyer's speed.

•6 wpm (min.) to 60 wpm (max.) can be set.



**19 SEMI BREAK-IN DELAY CONTROL [BK-IN DELAY]**

Adjusts the transmit-to-receive switching delay time for CW semi break-in operation.



**20 MODE SWITCHES**

Selects the desired mode. (p. 26)

•Announces the selected mode when an optional UT-102 is installed. (pgs. 71, 73)

SSB

- ➔ Selects USB and LSB mode alternately.
- ➔ Toggles SSB and SSB data mode (USB-D, LSB-D) when pushed for 2 sec.

CW/RTTY

- ➔ Selects CW and RTTY mode alternately.
- ➔ Toggles CW and CW-R (CW reverse) mode when pushed for 2 sec. in CW mode.

CW/RTTY

- ➔ Toggles RTTY and RTTY-R (RTTY reverse) mode when pushed for 2 sec. in RTTY mode.

AM/FM

- ➔ Selects AM and FM mode alternately.
- ➔ Toggles AM/FM and AM/FM data mode (AM-D, FM-D) when pushed for 2 sec.

**21 LCD FUNCTION SWITCHES [F-1]–[F-5]**

Push to select the function indicated in the LCD display above these switches.

•Functions vary depending on the operating condition.

**22 FILTER SWITCH [FILTER]**

➔ Selects one of 3 IF filter settings.

➔ Enters the filter set mode when pushed for 2 sec.

**23 EXIT SWITCH [EXIT]**

Exits from a set mode, etc. when pushed.

**24 SPEECH SWITCH [SPEECH]** (pgs. 71, 73)

Announces the selected readout frequency when an optional UT-102 is installed.

**25 TUNING DIAL** (p. 24)

Changes the displayed frequency, selects set mode items, etc.

**26 MAIN/SUB SWITCH [MAIN/SUB]**

Selects the main or sub readout for access.

•The sub readout frequency is displayed in outline or mesh font. The sub readout functions only during split operation or dualwatch.

**27 VFO/MEMORY SWITCH [VFO/MEMO]**

➔ Toggles the selected readout operating mode between the VFO mode and memory mode when pushed. (pgs. 23, 50)

➔ Transfers the memory contents to VFO when pushed for 2 sec. (p. 53)

**28 MAIN/SUB CHANGE SWITCH [CHANGE]**

- ➔ Toggles the frequency and selected memory channel between main and sub readouts when pushed.
  - Toggles between transmit frequency and receive frequency when the split frequency function is ON. (p. 32)
- ➔ Equalizes the sub readout frequency to the main readout frequency when pushed for 2 sec.

**29 MULTI-FUNCTION SWITCHES**

Push to select the functions indicated in the LCD display to the right of these switches.

- Functions vary depending on the operating condition.

- ➔ Toggles the antenna connector selection between ANT1/R and ANT2/R when pushed. (p. 45)



- ➔ Toggles the [RX ANT] (receive antenna) ON and OFF when pushed for 2 sec.

When a transverter is in use, this [ANT] does not function and 'TRV' appears.

- ➔ Selects RF power (Po), ALC, SWR or COMP metering during transmit. (p. 36)



- ➔ Toggles the multi-function digital meter ON and OFF when pushed for 2 sec.

- ➔ Selects one of 2 receive RF preamps or bypasses them.



- "P. AMP1" activates 10 dB preamp for HF all bands.
- "P. AMP2" activates 16 dB high-gain preamp for 21 MHz band and above.

**✓ What is the preamp?**

The preamp amplifies received signals in the front end circuit to improve the S/N ratio and sensitivity. Select "P. AMP1" or "P. AMP2" when receiving weak signals.

- ➔ Selects 6 dB, 12 dB or 18 dB attenuator, or bypasses them.



**✓ What is the attenuator?**

The attenuator prevents a desired signal from distorting when very strong signals are near the desired frequency, or when very strong electric fields, such as from a broadcasting station, are near your location.

- ➔ Activates or selects fast, middle or slow AGC time constant when pushed.



- "FAST" is only available for FM mode.
- ➔ Enters the AGC set mode when pushed for 2 sec.

AGC time constant can be set between 0.1 to 8.0 sec. (depends on mode), or turned OFF. While "OFF" is selected, the S-meter does not function.

**✓ What is the AGC?**

The AGC controls receiver gain to produce a constant audio output level, even when the received signal strength is varied by fading, etc. Select "FAST" for tuning and select "MID" or "SLOW" depending on the receiving condition.

- ➔ Turns the VOX function ON and OFF when pushed in non-CW modes. (p. 35)



- ➔ Enters the VOX set mode when pushed for 2 sec. in non-CW modes. (p. 35)

**✓ What is the VOX function?**

The VOX function (voice operated transmission) starts transmission without pushing the transmit switch or PTT switch when you speak into the microphone; then, automatically returns to receive when you stop speaking.

- ➔ Selects semi break-in, full break-in operation, or turns the break-in operation OFF when pushed in CW mode.



**✓ What is the break-in function?**

The break-in function toggles transmit and receive with CW keying. Full break-in (QSK) can monitor the receive signal during keying.

- ➔ Turns the RTTY filter ON and OFF in RTTY mode. (p. 28)



- When the RTTY filter is turned ON, [TWIN PBT] functions as the IF shift control.
- ➔ Enters the RTTY filter set mode when pushed for 2 sec. in RTTY mode. (p. 28)

**✓ What is the IF shift?**

The IF shift function electronically changes the center of the IF (Intermediate Frequency) passband frequency to reject interference. Only the inner control of [TWIN PBT] can be used for the IF shift control.

- ➔ Turns the speech compressor ON and OFF in SSB mode. (p. 37)



- ➔ Toggles the narrow, middle or wide transmit filter when pushed for 2 sec.

**✓ What is the speech compressor?**

The speech compressor compresses the transmitter audio input to increase the average audio output level. Therefore, talk power is increased. This function is effective for long distance communication or when propagation conditions are poor.

- ➔ Turns the 1/4 function ON and OFF in CW and RTTY modes. (p. 25)




- 1/4 function sets dial rotation to 1/4 of normal for fine tuning.

- ➔ Toggles the tone encoder, tone squelch function and no tone operation when pushed in FM mode. (pgs. 46, 47)



- ➔ Enters the tone set mode when pushed for 2 sec. in FM mode. (pgs. 46, 47)


■ Front panel (continued)



**28 LOCK SWITCH [LOCK]** (p. 45)  
Turns the dial lock function ON and OFF.

**29 RIT/ΔTX CONTROL [RIT/ΔTX]** (p. 34)  
Shifts the receive and/or transmit frequency without changing the transmit and/or receive frequency while the RIT and/or ΔTX functions are ON.

- Rotate the control clockwise to increase the frequency, or rotate the control counterclockwise to decrease the frequency.
- The shift frequency range is ±9.999 kHz in 1 Hz steps (or ±9.99 kHz in 10 Hz steps).



**30 RIT SWITCH [RIT]** (p. 34)  
Turns the RIT function ON and OFF when pushed.

- Use the [RIT/ΔTX] control to vary the RIT frequency.
- Adds the RIT shift frequency to the operating frequency when pushed for 2 sec.

**What is the RIT function?**  
The RIT (Receiver Incremental Tuning) shifts the receive frequency without shifting the transmit frequency.

This is useful for fine tuning stations calling you on an off-frequency or when you prefer to listen to slightly different-sounding voice characteristics, etc.


**31 ΔTX SWITCH [ΔTX]** (p. 34)  
Turns the ΔTX function ON and OFF when pushed.

- Use the [RIT/ΔTX] control to vary the ΔTX frequency.
- Adds the ΔTX shift frequency to the operating frequency when pushed for 2 sec.

**What is the ΔTX function?**  
The ΔTX shifts the transmit frequency without shifting the receive frequency. This is useful for simple split frequency operation in CW, etc.


**32 CLEAR SWITCH [CLEAR]** (p. 34)  
Clears the RIT/ΔTX shift frequency when pushed for 2 sec.

**33 CW PITCH CONTROL [CW PITCH]** (outer control; p. 29)  
Shifts the received CW audio pitch and monitored CW audio pitch without changing the operating frequency.



**34 MANUAL NOTCH FILTER CONTROL [NOTCH]** (inner control; p. 27)  
Varies the peak frequency of the manual notch filter to pick out a receive signal from interference while the manual notch function is ON.

- Notch filter center frequency:
  - SSB : 0 Hz to 5100 Hz
  - CW : -900 Hz + CW pitch freq. to 4200 Hz + CW pitch freq.
  - AM : -5100 Hz to 5100 Hz





- 35 PBT CLEAR SWITCH [PBT CLR]** (p. 26)  
Clears the PBT settings when pushed for 2 sec.  
•The [PBT CLR] indicator appears when PBT is in use.

- 36 NOTCH SWITCH [NOTCH]** (p. 27)
  - ➔Toggles the notch function between auto, manual and OFF in SSB and AM modes.
  - ➔Turns the manual notch function ON and OFF when pushed in CW mode.
  - ➔Turns the auto notch function ON and OFF when pushed in FM mode.
    - “AN” appears when auto notch is in use.
    - “MN” appears when manual notch is in use.

✓ **What is the notch function?**


The notch function eliminates unwanted CW or AM carrier tones while preserving the desired signal's audio response. The filtering frequency is adjusted to effectively eliminate unwanted tones via the DSP circuit.



- 37 PASSBAND TUNING CONTROLS [TWIN PBT]**  
Adjust the receiver's "passband width" of the DSP filter. (p. 26)
  - Passband width and shift frequency are displayed in the LCD.
  - Push [PBT CLR] for 2 sec. to clear the settings when not in use.
  - Variable range is set to the half of the IF filter passband width. 25 Hz steps and 50 Hz steps are available.
  - These controls function as an IF shift control while in AM mode and when the RTTY filter is turned ON. Only the inner control may function in this case.

✓ **What is the PBT control?**

General PBT function electronically narrows the IF passband width to reject interference. This transceiver uses the DSP circuit for the PBT function.



- 38 LOCK INDICATOR [LOCK]** (p. 45)  
Lights when the dial lock function is activated.

- 39 MEMO PAD-READ SWITCH [MP-R]** (p. 55)  
Each push calls up a frequency and operating mode in a memo pad. The 5 (or 10) most recently programmed frequencies and operating modes can be recalled, starting from the most recent.  
•The memo pad capacity can be expanded from 5 to 10 in set mode for your convenience. (p. 71)

- 40 KEYPAD**
  - ➔Pushing a key selects the operating band.
    - [GENE] selects the general coverage band.
  - ➔Pushing the same key 2 or 3 times calls up other stacked frequencies in the band. (p. 24)
    - Icom's triple band stacking register memorizes 3 frequencies in each band.
  - ➔After pushing [F-INP], enters a keyed frequency or memory channel. Pushing [(F-INP)ENT] or [▲]/[▼] is necessary at the end. (pgs. 24, 50)
    - e.g. to enter 14.195 MHz, push [F-INP] [1] [4] [.] [1] [9] [5] [(F-INP)ENT].

- 41 MEMO PAD-WRITE SWITCH [MP-W]** (p. 55)  
Programs the selected readout frequency and operating mode into a memo pad.
  - The 5 most recent entries remain in memo pads.
  - The transmit frequency is programmed when pushed together with [XFC].
  - The memo pad capacity can be expanded from 5 to 10 in set mode for your convenience. (p. 71)


- 42 DUALWATCH SWITCH [DUALWATCH]** (p. 31)
  - ➔Turns the dualwatch function ON and OFF when pushed.
  - ➔Turns the dualwatch function ON and equalizes the sub readout frequency to the main readout when pushed for 2 sec. (Quick dualwatch function)
    - The quick dualwatch function can be turned OFF using set mode. (p. 68)

- 43 SPLIT SWITCH [SPLIT]** (p. 32)
  - ➔Turns the split function ON and OFF when pushed.
  - ➔Turns the split function ON, equalizes the sub readout frequency to the main readout and sets the sub readout for frequency input when pushed for 2 sec. in non-FM modes. (Quick split function)
    - The offset frequency is shifted from the main readout frequency in FM mode. (pgs. 46, 69)
    - The quick split function can be turned OFF using set mode. (p. 68)
  - ➔Turns the split function ON and shifts the sub readout frequency after inputting an offset ( $\pm 4$  MHz in 1 kHz steps).

- 44 RECEIVE INDICATOR [RX]**  
Lights green while receiving a signal and when the squelch is open.

- 45 TRANSMIT INDICATOR [TX]**  
Lights red while transmitting.

■ Front panel (continued)




**46 LCD FUNCTION DISPLAY** (See p. 10 for details.) Shows the operating frequency, function switch menus, spectrum screen, memory channel screen, set mode settings, etc.

**47 MEMORY UP/DOWN SWITCHES [▲]/[▼]** (p. 50)  
 ➔ Select the memory channel number for the selected readout.  
 •Memory channels can be selected both in VFO and memory modes.  
 ➔ Select the desired memory channel directly after pushing [F-INP] and a memory channel number.

**48 MEMORY WRITE SWITCH [MW]** (p. 52)  
 Stores the selected readout frequency and operating mode into the displayed memory channel when pushed for 2 sec.  
 •This function is available both in VFO and memory modes.

**49 MEMORY CLEAR SWITCH [M-CL]** (p. 54)  
 Clears the selected readout memory channel contents when pushed for 2 sec. in memory mode.  
 •The channel becomes a blank channel.  
 •This switch does not function in VFO mode.


**50 QUICK TUNING SWITCH [TS]** (p. 25)  
 ➔ Turns the quick tuning step ON and OFF.  
 •While the quick tuning indicator is displayed, the frequency can be changed in programmed kHz steps.  
 •0.1, 1, 5, 9, 10, 12.5, 20 and 25 kHz quick tuning steps are available.



➔ While the quick tuning step is OFF, turns the 1 Hz step ON and OFF when pushed for 2 sec.  
 •1 Hz indications appear in both readouts and the frequency can be changed in 1 Hz steps.  
 ➔ While the quick tuning step is ON, enters the quick tuning step set mode when pushed for 2 sec.

**51 TRANSMIT FREQUENCY CHECK SWITCH [XFC]**  
 Monitors the transmit frequency when pushed and held when the split frequency function is ON.  
 •While pushing this switch, the transmit frequency can be changed with the tuning dial, keypad, memo pad or the [▲]/[▼] switches.  
 •When the split lock function is turned ON, pushing [XFC] cancels the dial lock function. (p. 69)

## ■ Microphone (HM-36)



### ① UP/DOWN SWITCHES [UP]/[DN]

Change the selected readout frequency or memory channel.


- Continuous pushing changes the frequency or memory channel number continuously.
- While pushing [XFC], the transmit readout frequency can be controlled while in split frequency operation.
- The [UP]/[DN] switch can simulate a key paddle. Preset in the keyer set mode. (p. 42)

### ② PTT SWITCH

Push and hold to transmit; release to receive.

## • MICROPHONE CONNECTOR


(Front panel view)




[MIC] PIN NO.	FUNCTION	DESCRIPTION
②	+8 V DC output	Max. 10 mA
③	Frequency up	Ground
	Frequency down	Ground through 470 Ω
④	Squelch open	"LOW" level
	Squelch closed	"HIGH" level

**CAUTION: DO NOT** short pin 2 to ground as this can damage the internal 8 V regulator.

## • HM-36 SCHEMATIC DIAGRAM



## ■ LCD display



### 1 TX INDICATOR

Indicates the frequency readout for transmit.

### 2 VFO/MEMORY CHANNEL INDICATOR

(pgs. 23, 50)

Indicates the VFO mode or selected memory channel number.

### 3 SELECT MEMORY CHANNEL INDICATOR

(p. 59)

Indicates the displayed memory channel is set as a select memory channel.

### 4 MULTI-FUNCTION SWITCH GUIDE

Indicates the function of the multi-function switches.

### 5 LCD FUNCTION SWITCH GUIDE

Indicates the function of the LCD function switches ([F-1]–[F-5]).

### 6 MULTI-FUNCTION SCREEN (p. 11)

Shows the screens for the multi-function digital meter, spectrum scope, voice recorder, memory channel, scan, memory keyer, RTTY decoder, IF filter selection or set modes, etc.

### 7 MEMORY CHANNEL READOUTS (p. 50)

- ➔ Show the selected memory channel contents in VFO mode.
- ➔ Show the VFO contents in memory mode.

### 8 FREQUENCY READOUTS (p. 24)

Show the operating frequency.

- Outline characters are used for non-accessing readout.

### 9 CLOCK READOUT (p. 62)

Shows the current time.

### 10 RTTY TUNING INDICATOR (p. 41)

Shows the tuning level in RTTY mode.

### 11 QUICK TUNING INDICATOR (p. 25)

Appears when the quick tuning step function is in use.

### 12 PASSBAND WIDTH INDICATOR (p. 26)

Graphically displays the passband width for twin PBT operation and center frequency for IF shift operation.

### 13 IF FILTER INDICATOR (p. 29)

Shows the selected IF filter number.

### 14 SHIFT FREQUENCY INDICATOR (p. 26)

Shows the shift frequency of the IF filter.

### 15 MODE INDICATOR (p. 26)

Shows the selected mode.

### 16 BAND WIDTH INDICATOR (p. 29)


Shows the passband width of the IF filter.

## ■ Screen menu arrangement


The following screens can be selected from the start up screen. Choose the desired screen using the following chart.

Pushing [EXIT] one or more times returns to the start up screen. See p. 64 for set mode arrangement.

### •Start up screen




### •Spectrum scope screen (p. 44)




F-1

### •Voice recorder screen (p. 38)



F-2

### •Programmed scan screen (p. 57)



F-4

### •Memory keyer screen (p. 42)




F-2

### •Memory channel scan screen (p. 58)




F-4

### •RTTY decoder screen (p. 41)




F-2

### •Set mode screen (p. 64)




F-5

### •Memory channel screen (p. 51)



F-3

## ■ Rear panel



**1 RECEIVE ANTENNA CONNECTOR [RX ANT]**

(p. 16)  
Connects a 50 Ω general coverage antenna with an RCA connector.

**2 TRANSVERTER JACK [XVERT]** (p. 19)

External transverter input/output jack. Activated by voltage applied to [ACC(2)] pin 6.

**3 TUNER CONTROL SOCKET [TUNER]** (p. 16)

Accepts the control cable from an optional AH-4 HF/50 MHz AUTOMATIC ANTENNA TUNER or AH-3 HF AUTOMATIC ANTENNA TUNER.


**4 ACCESSORY SOCKET 1 [ACC(1)]**

**5 ACCESSORY SOCKET 2 [ACC(2)]**

Enable connection of external equipment such as a linear amplifier, an automatic antenna selector/tuner, TNC for data communications, etc.  
• See p. 13 for socket information.

**6 STRAIGHT KEY JACK [KEY]** (p. 15)

Accepts a straight key or external electronic keyer with ¼ inch standard plug.  
• [ELEC-KEY] on the front panel can be used for a straight key or external electronic keyer. Deactivate the internal electronic keyer in keyer set mode. (p. 42)



/// If you use an external electronic keyer, make sure the voltage retained by the keyer is less than 0.4 V when the key is ON.

**7 CI-V REMOTE CONTROL JACK [REMOTE]**

(p. 16)  
➤ Designed for use with a personal computer for remote control of transceiver functions.  
➤ Used for transceive operation with another Icom CI-V transceiver or receiver.

**8 EXTERNAL SPEAKER JACK [EXT SP]**

(pgs. 16, 81)  
Accepts an 4–8 Ω speaker.

**9 ALC INPUT JACK [ALC]** (p. 19)


Connects to the ALC output jack of a non-Icom linear amplifier.

**10 SEND CONTROL JACK [SEND]** (p. 19)

Goes to ground while transmitting to control external equipment such as a linear amplifier.  
• Max. control level: 16 V DC/2 A

**11 DC POWER SOCKET [DC 13.8V]** (p. 15)

Accepts 13.8 V DC through the supplied DC power cable (OPC-025D).



**12 ANTENNA CONNECTOR 1 [ANT1]**


**13 ANTENNA CONNECTOR 2 [ANT2]** (pgs. 14, 15)  
Accept a 50 Ω antenna with a PL-259 connector.


**14 GROUND TERMINAL [GND]** (pgs. 14, 15)

Connect this terminal to a ground to prevent electrical shocks, TVI, BCI and other problems.

When using an optional AH-4 HF/50 MHz AUTOMATIC ANTENNA TUNER or AH-3 HF AUTOMATIC ANTENNA TUNER, connect it to the [ANT1] connector. The internal antenna tuner activates for [ANT2] and deactivates for [ANT1] when connecting the AH-4 or AH-3.

**◇ ACC SOCKETS**

ACC(1)	PIN NO.	PIN NAME	DESCRIPTION	SPECIFICATIONS
 Rear panel view	1	RTTY	Controls RTTY keying.	"HIGH" level : More than 2.4 V "LOW" level : Less than 0.6 V Output current : Less than 2 mA
	2	GND	Connects to ground.	Connected in parallel with ACC(2) pin 2.
	3	SEND	Input/output pin. Goes to ground when transmitting. When grounded, transmits.	Ground level : -0.5 V to 0.8 V Output current : Less than 20 mA Input current (Tx) : Less than 200 mA Connected in parallel with ACC(2) pin 3.
	4	MOD	Modulator input. Connects to a modulator.	Input impedance : 10 kΩ Input level : Approx. 100 mV rms
	5	AF	AF detector output. Fixed, regardless of [AF] position in default settings. (see notes below)	Output impedance : 4.7 kΩ Output level : 100 to 300 mV rms
	6	SQLS	Squelch output. Goes to ground when squelch opens.	Squelch open : Less than 0.3 V/5 mA Squelch closed : More than 6.0 V/100 μA
	7	13.8 V	13.8 V output when power is ON.	Output current : Max. 1 A Connected in parallel with ACC(2) pin 7.
	8	ALC	ALC voltage input.	Control voltage : -4 to 0 V Input impedance : More than 10 kΩ Connected in parallel with ACC(2) pin 5.

ACC(2)	PIN NO.	PIN NAME	DESCRIPTION	SPECIFICATIONS
 Rear panel view	1	8 V	Regulated 8 V output.	Output voltage : 8 V ±0.3 V Output current : Less than 10 mA
	2	GND	Same as ACC(1) pin 2.	
	3	SEND	Same as ACC(1) pin 3.	
	4	BAND	Band voltage output. (Varies with amateur band)	Output voltage : 0 to 8.0 V
	5	ALC	Same as ACC(1) pin 8.	
	6	TRV	Activates [XVERT] input/output when "HIGH" voltage is applied.	Input impedance : More than 10 kΩ Input voltage : 2 to 13.8 V
	7	13.8 V	Same as ACC(1) pin 7.	

If the CW side tone level limit or beep level limit is in use, the CW side tone or beep tone decreases from the fixed level when the [AF] control is rotated above a specified level, respectively. (p. 65)

# 3

## INSTALLATION AND CONNECTIONS

### ■ Unpacking


After unpacking, immediately report any damage to the delivering carrier or dealer. Keep the shipping cartons.

For a description and a diagram of accessory equipment included with the IC-756PRO, see 'Supplied accessories' on p. 1 of this manual.

### ■ Selecting a location

Select a location for the transceiver that allows adequate air circulation, free from extreme heat, cold, or vibrations, and away from TV sets, TV antenna elements, radios and other electro-magnetic sources.

The base of the transceiver has an adjustable stand for desktop use. Set the stand to one of two angles depending on your operating conditions.




### ■ Grounding

To prevent electrical shock, television interference (TVI), broadcast interference (BCI) and other problems, ground the transceiver through the GROUND terminal on the rear panel.

For best results, connect a heavy gauge wire or strap to a long earth-sunk copper rod. Make the distance between the [GND] terminal and ground as short as possible.

**WARNING: NEVER** connect the [GND] terminal to a gas or electric pipe, since the connection could cause an explosion or electric shock.




### ■ Antenna connection

For radio communications, the antenna is of critical importance, along with output power and sensitivity. Select antenna(s), such as a well-matched 50 Ω antenna, and feedline. 1.5:1 or better of Voltage Standing Wave Ratio (VSWR) is recommended for your desired band. Of course, the transmission line should be a coaxial cable.

When using 1 antenna, use the [ANT1] connector.

**CAUTION:** Protect your transceiver from lightning by using a lightning arrester.

#### PL-259 CONNECTOR INSTALLATION EXAMPLE




#### Antenna SWR

Each antenna is tuned for a specified frequency range and SWR may be increased out-of-range. When the SWR is higher than approx. 2.0:1, the transceiver's power drops to protect the final transistor. In this case, an antenna tuner is useful to match the transceiver and antenna. Low SWR allows full power for transmitting even when using the antenna tuner. The IC-756PRO has an SWR meter to monitor the antenna SWR continuously.




## ■ Required connections

### •Front panel




### •Rear panel




## ■ Advanced connections

### • Front panel



### • Rear panel




## ■ Power supply connections

Use an optional DC power supply with a 25 A capacity and above when operating the transceiver with AC power. Refer to the diagrams below.


**CAUTION:** Before connecting the DC power cable, check the following important items. Make sure:

- The [POWER] switch is OFF.
- Output voltage of the power source is 12–15 V when you use a non-Icom power supply.
- DC power cable polarity is correct.
  - Red : positive ⊕ terminal
  - Black : negative ⊖ terminal

### CONNECTING A DC POWER SUPPLY




### CONNECTING A VEHICLE BATTERY



### Linear amplifier connections


Use the [ANT1] connector when connecting a linear amplifier.

#### CONNECTING THE IC-PW1



Turn OFF the transceiver's antenna tuner while tuning the IC-PW1's tuner.

#### CONNECTING THE IC-4KL




Turn OFF the transceiver's antenna tuner while tuning the IC-4KL's tuner.

**CONNECTING THE IC-2KL**

**CAUTION:**

Set the transceiver output power for 80 W max. with the [RF POWER] control, otherwise, a protection circuit will activate.




**CONNECTING A NON-ICOM LINEAR AMPLIFIER**

**WARNING:**

Set the transceiver output power and linear amplifier ALC output level referring to the linear amplifier instruction manual.

The ALC input level must be in the range 0 V to -4 V, and the transceiver does not accept positive voltage. Non-matched ALC and RF power settings could cause a fire or ruin the linear amplifier.




The specifications for the SEND relay are 16 V DC 2 A. If this level is exceeded, a large external relay must be used.

**Transverter jack information**

When 2 to 13.8 V is applied to pin 6 of [ACC(2)], the [XVERT] jack is activated for transverter operation and the antenna connectors do not receive or transmit any signals. (p. 13)


While receiving, the [XVERT] jack can be activated as an input terminal from an external transverter.

While transmitting, the [XVERT] jack outputs signals of the displayed frequency at -20 dBm (22 mV) as signals for the external transverter.




## External antenna selector or antenna tuner connections

### CONNECTING THE EX-627




### CONNECTING THE AH-4 or AH-3

- The AH-4 and AH-3 must be connected to [ANT1].
- The AH-3 can be used for the HF bands only, although the [ANT1] connector is used for both HF and 50 MHz operation. Use a coaxial antenna switch when you operate the 50 MHz band with the AH-3 connected.



### CONNECTING THE IC-AT500 THROUGH THE IC-2KL



## ■ FSK and AFSK (SSTV) connections


To connect a terminal unit, TNC or scan converter, refer to the diagram below.

### For RTTY operation:

Narrow filter settings may not pass RTTY signals.  
Be sure to select the appropriate IF filter settings corresponding to the signal width. (p. 29)

### FSK (RTTY) connection


Use RTTY mode for operation



\* Connect the SQUELCH line when required.

### AFSK and SSTV connections


Use SSB or FM mode for operation



\* Connect the SQUELCH line when required.

### AFSK and SSTV connections via microphone connector

Use SSB or FM mode for operation



\* Connect the SQUELCH line when required.


When connected to the [MIC] connector, [MIC GAIN] and [AF] control adjustment is required.

## ■ When first applying power (CPU resetting)

Before first applying power, make sure all connections required for your system are complete by referring to Chapter 3. Then, reset the transceiver using the following procedure.

Resetting **CLEARs** all programmed contents in memory channels and returns programmed values in set mode to default values.

- ① Make sure the transceiver power is OFF.
- ② While pushing [M-CL] and [F-INP], push [POWER] for 2 sec. to turn power ON.
  - The internal CPU is reset.
  - A/D convertor calibration of the DSP unit starts and it takes 10 sec.
  - The transceiver displays its initial VFO frequencies when resetting is complete.
- ③ Correct the set mode settings after resetting, if desired.




Under cooler temperatures, the LCD may appear dark and unstable after turning power ON. This is normal and does not indicate any equipment malfunction.

## ■ Initial settings

After resetting the transceiver, set controls and switches as shown in the figure below.

CW : Max. clockwise  
CCW : Max. counterclockwise



Turn power ON, then check the display. If any of the following indicators appear, turn them OFF as follows:

- Quick tuning step indicator “▼” : Push [TS].
- 1 Hz frequency readout : Push [TS] for 2 sec. (while quick tuning step is OFF)
- RIT indicator “**RIT**” : Push [RIT].
- ΔTX indicator “**ΔTX**” : Push [ΔTX].
- Split indicator “**SPLIT**” : Push [SPLIT].
- Dualwatch indicator “**DUAL-W**” : Push [DUAL WATCH].
- Twin peak filter indicator “**TPF**” : Push [RTTY FIL].
- Auto notch indicator “**AN**” : Push [NOTCH].
- Manual notch indicator “**MN**” : Push [NOTCH].




## VFO description

VFO is an abbreviation of Variable Frequency Oscillator, and traditionally refers to an oscillator.

The transceiver's VFO is somewhat different. The VFO of the IC-756PRO acts like a computer's window and can show one frequency and one operating mode.

You can call up a desired frequency to the VFO with the keypad, memo pad-read switch (see p. 55) or the memory transfer function (see p. 53). You can also change the frequency with the tuning dial and select the operating mode with the mode switches.

During dualwatch or split frequency operation, the sub VFO is functional (non-outline, non-spotted, larger frequency characters). While pushing [XFC] during split frequency operation, you can change the transmit readout frequency with the keypad, memo pad-read switch or the memory transfer function.



### • Differences between VFO mode and memory mode


#### VFO MODE

VFO shows a frequency and operating mode. If the frequency or operating mode is changed, the VFO automatically memorizes the new frequency or new operating mode.


When a VFO is selected from another band or memory mode, the frequency and operating mode last used for that VFO appear.

#### [EXAMPLE]


VFO is selected.




The frequency is changed.



Memory mode is selected.



VFO is selected again.



Changed frequency (14.123 MHz) appears.


#### MEMORY MODE (pgs. 50–54)

Each memory channel shows a frequency and operating mode like a VFO. Even if the frequency or mode is changed, the memory channel does not memorize the new frequency or operating mode.


When the memory channel is selected from another memory channel or VFO mode, the memorized frequency and operating mode appear.

#### [EXAMPLE]


Memory channel 1 is selected.




The frequency is changed.



Another memory channel is selected.



Memory channel 1 is selected again.




Changed frequency (14.123 MHz) does not appear and memorized frequency (14.100 MHz) appears instead.


## Frequency setting with the tuning dial

### •For ham band use

- Push the desired band key on the keypad 1–3 times.
  - 3 different frequencies can be selected on each band with the band key. (See “Triple band stacking register” below.)



- Rotate the tuning dial to set the desired frequency.




- Select the desired operating mode with the mode switch. (p. 26)


/// If the dial lock function is activated, the lock indicator lights, and the tuning dial does not function. In this case, push [LOCK] to deactivate the lock function.

### •For general coverage receiver use

- Push [GENE] on the keypad 1–3 times.
  - The [GENE] key calls up a frequency for general coverage receiver use.



- Rotate the tuning dial to set the desired frequency.
  - For quick tuning, use the quick tuning step function. (p. 25)



- Select the desired operating mode with the mode switch. (p. 26)


### TRIPLE BAND STACKING REGISTER

The triple band stacking register provides 3 memories in one band. 3 sets of a frequency and mode on each band are automatically stored when used.

If a band key is pushed once, the frequency and mode last used are called up. When the key is pushed again, another stored frequency and mode are called up.

This function is convenient when you operate 3 modes on one band. For example, one register is used for a CW frequency, another for an SSB frequency and the other one for an RTTY frequency.

### [EXAMPLE]



## Direct frequency entry with the keypad

The transceiver has a keypad for direct frequency entry as described below.

- Push [F-INP].
  - “F-Inp” appears.
- Input the desired frequency.
  - Input “.” (decimal point) between the MHz units and kHz units.
- Push [(F-INP)ENT] to enter the input frequency.
  - To cancel the input, push [MAIN/SUB] instead of [(F-INP)ENT].

### [EXAMPLE]


- 14.025 MHz: [F-INP] [1] [4] [.] [0] [2] [5] [ENT]
- 18.0725 MHz: [F-INP] [1] [8] [.] [0] [7] [2] [5] [ENT]
- 706 kHz: [F-INP] [.] [7] [0] [6] [ENT]
- 5.100 MHz: [F-INP] [5] [.] [1] [ENT]
- 7.000 MHz: [F-INP] [7] [ENT]
- 21.280 → 21.245: [F-INP] [.] [2] [4] [5] [ENT]

## ■ Advanced tuning functions


### QUICK TUNING STEP

The operating frequency can be changed in kHz steps (0.1, 1, 5, 9, 10, 12.5, 20 or 25 kHz selectable) for quick tuning.

- 1 Push [TS] momentarily to display the quick tuning indicator.




- 2 Rotate the tuning dial to change the frequency in programmed kHz steps.
- 3 Push [TS] again to turn OFF the indicator.
- 4 Rotate the tuning dial for normal tuning if desired.



### SELECTING THE kHz STEP

- 1 Push [TS] momentarily to turn the quick tuning step ON.
- 2 Push [TS] for 2 sec. to enter the quick tuning step setting display.
  - Selected tuning steps for all modes appear.





- 3 Select the desired operating mode.
- 4 Rotate the tuning dial to select the desired tuning step from 0.1, 1, 5, 9, 10, 12.5, 20 or 25 kHz.
- 5 Repeat steps 3 and 4 to select quick tuning steps for other modes, if desired.
- 6 Push [EXIT] to exit the setting display.

### SELECTING THE 1 Hz STEP

The minimum tuning step of 1 Hz can be used for fine tuning.

- 1 Turn OFF the quick tuning step.
  - "▼" does not appear.
- 2 Push [TS] for 2 sec. to toggle the 1 Hz tuning step ON and OFF.
  - RIT and/or ΔTX also functions in 1 Hz tuning step when used.



### 1/4 TUNING STEP FUNCTION (CW/RTTY only)

While operating in CW/RTTY, the 1/4 function is available for critical tuning. Dial rotation is reduced to 1/4 of normal when the 1/4 function is in use.

➔ Push [1/4] to toggle the 1/4 function ON and OFF.

1/4 tuning step OFF



1/4 tuning step ON



### AUTO TUNING STEP FUNCTION (AM/FM only)

When selecting AM or FM, the quick tuning step is automatically selected by the auto tuning step function.

## Mode selection


The following modes are available in the IC-756PRO:

SSB (LSB/USB), CW, CW-R (CW reverse), RTTY, RTTY-R (RTTY reverse), AM and FM. Data modes of SSB, AM and FM are also available.

Microphone signals are muted when data mode is selected.

To select a mode of operation, push the desired mode switch momentarily. Push the switch again to toggle between USB and LSB, CW/CW-R and RTTY/RTTY-R, AM and FM, if necessary. Push the switch for 2 sec. to toggle between normal and data mode, CW and CW-R, RTTY and RTTY-R, if necessary.

See the diagram below for the order of selection.



## Twin PBT operation


General PBT (Passband Tuning) function electronically narrows the IF passband width by shifting the IF frequency to slightly outside of the IF filter passband to reject interference. This transceiver uses the DSP circuit for the PBT function. Moving both [TWIN PBT] controls to the same position shifts the IF.

- ➔ The LCD shows the passband width and shift frequency graphically.
- ➔ Push [FILTER] for 2 sec. to enter the filter set mode. Current passband width and shift frequency is displayed in the filter set mode screen.
- ➔ To set the [TWIN PBT] controls to the center positions, push [PBT CLR] for 2 sec.

The variable range depends on the passband width and mode. The edge of the variable range is half of the passband width, and PBT is adjustable in 25 or 50 Hz steps. These controls function as an IF shift control while in AM mode and when the RTTY filter is turned ON. Only the inner control may function in this case. IF shift is adjustable in 20/40 Hz steps in RTTY (RTTY filter is turned ON) or 150/300/500 Hz steps in AM.

- [TWIN PBT] should normally be set to the center positions (PBT setting is cleared) when there is no interference.
- When PBT is used, the audio tone may be changed.
- Not available for FM mode.
- While rotating [TWIN PBT], noise may occur. This comes from the DSP unit and does not indicate an equipment malfunction.

### PBT OPERATION EXAMPLE




## ■ Notch function

This transceiver has auto and manual notch functions. The auto notch function automatically attenuates more than 3 beat tones, tuning signals, etc., even if they are moving. The manual notch can be set to attenuate a frequency via the [NOTCH] control.

- ➔ Push [NOTCH] to toggle the notch function between auto, manual and OFF in SSB and AM modes.
- ➔ Push [NOTCH] to turn the manual notch function ON and OFF in CW mode.
- ➔ Push [NOTCH] to turn the auto notch function ON and OFF in FM mode.
  - Set to attenuate a frequency for manual notch via the [NOTCH] control.
  - “AN” appears when auto notch is in use.
  - “MN” appears when manual notch is in use.

While operating the manual notch, noise may be heard. This comes from the DSP unit and does not indicate an equipment malfunction.




## ■ Noise reduction

The noise reduction function reduces noise components and picks out desired signals which are buried in noise. The received signals are converted to digital signals and then the desired signals are separated from the noise.

- ① Push the [NR] switch to turn the noise reduction ON.
  - [NR] indicator lights.
- ② Rotate the [NR] control to adjust the noise reduction level.
- ③ Push the [NR] switch to turn the noise reduction OFF.
  - [NR] indicator does not light.


Deep rotation of the [NR] control results in audio signal masking or distortion. Set the [NR] control for maximum readability.




## ■ Noise blanker

The noise blanker eliminates pulse-type noise such as from car ignitions. The noise blanker is not available for FM mode.

- ➔ Push the [NB] switch to turn the noise blanker ON or OFF.



When using the noise blanker, received signals may be distorted if they are excessively strong.



## RTTY filter/Twin peak filter

The transceiver has 5 RTTY filters in addition to normal IF filters. The passband width can be selected from 1 kHz, 500 Hz, 350 Hz, 300 Hz and 250 Hz. When the RTTY filter is turned ON, the RTTY tuning meter can be used. (p. 41)



Moreover, the twin peak filter changes the receive frequency response by boosting 2 particular frequencies (2125 and 2295 Hz) for better copying of desired RTTY signals.

- ① Push [CW/RTTY] once or twice to select RTTY mode.
- ② Push [RTTY FIL] to turn the RTTY filter ON.
  - “TPF” appears when the twin peak filter is turned ON.

### RTTY filter selection

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select RTTY mode.
- ③ Push [RTTY FIL] for 2 sec. to enter RTTY filter set mode.
- ④ Push [(F-1)▲] to select band width item.
- ⑤ Rotate the tuning dial to select the RTTY filter width from 1 kHz, 500 Hz, 350 Hz, 300 Hz and 250 Hz.

- Push [(F-3)DEF] for 2 sec. to select a default value.
- ⑥ Push [(F-2)▼] to select twin peak filter item.
    - The received audio volume may become greater when the twin peak filter is turned ON.
  - ⑦ Rotate the tuning dial to turn the twin peak filter function ON or OFF.
  - ⑧ Push [EXIT] to exit the RTTY filter set mode.




## CW reverse mode

CW-R (CW Reverse) mode receives CW signals with a reverse side CW carrier point like that of LSB and USB modes.

Use when interfering signals are near a desired signal and you want to change the interference tone.

- ① Push [CW/RTTY] once or twice to select CW mode.
- ② Push [CW/RTTY] for 2 sec. to select CW or CW-R mode.
  - Check the interfering tone.

### Receive audio tone response



## RTTY reverse mode

Received characters are occasionally garbled when the receive signal is reversed between MARK and SPACE. This reversal can be caused by incorrect TNC connections, settings, commands, etc.

To receive a reversed RTTY signal correctly, select RTTY-R (RTTY Reverse) mode.

- ① Push [CW/RTTY] once or twice to select RTTY mode.
- ② Push [CW/RTTY] for 2 sec. to select RTTY or RTTY-R mode.
  - Check the receive signal.

## ■ CW pitch control

The received CW audio pitch and monitored CW audio can be adjusted to suit your preferences (300 to 900 Hz) without changing the operating frequency.

The received CW audio pitch can be adjusted in 25 Hz steps.

▨ The filter set mode screen graphically displays the CW pitch operations. (See below.)

## ■ IF filter selection

The transceiver has 3 passband width IF filters for each mode.

For SSB and CW modes, the passband width can be set within 50 to 3600 Hz in 50 or 100 Hz steps. A total of 41 passband widths are available.

For RTTY mode, the passband width can be set within 50 to 2700 Hz in 50 or 100 Hz steps. A total of 32 passband widths are available.


For AM and FM modes, the passband width is fixed and 3 passband widths are available.

▨ The filter selection is automatically memorized in each mode.

▨ The PBT shift frequencies are automatically memorized in each filter.


### •IF filter selection

- ① Select the desired mode.
- ② For RTTY mode, turn OFF the RTTY filter by pushing [RTTY FIL].
- ③ Push [FILTER] one or more times to select the IF filter 1, 2 or 3.
  - The selected passband width and filter number is displayed in the LCD.



### •Filter passband width setting (SSB, CW and RTTY mode only)

- ① Select SSB, CW or RTTY mode.
  - Passband widths for AM and FM modes are fixed and cannot be set.
- ② For RTTY mode, turn OFF the RTTY filter by pushing [RTTY FIL].
- ③ Push [FILTER] for 2 sec. to enter filter set mode.



- ④ Push [FILTER] one or more times to select the desired IF filter.
- ⑤ While pushing [(F-1)BW], rotate the tuning dial to set the desired passband width.
  - In SSB and CW modes, the passband width can be set within the following range.
 

50 to 500 Hz	50 Hz steps
600 to 2700 Hz	100 Hz steps
  - In RTTY mode, the passband width can be set within the following range.
 

50 to 500 Hz	50 Hz steps
600 to 2700 Hz	100 Hz steps
  - Push [(F-3)DEF] to select the default value.
- ⑥ Repeat steps ④ to ⑤ if desired.
- ⑦ Push [EXIT] to exit the filter set mode screen.

▨ The PBT shift frequencies are cleared when the passband width is changed.

▨ This filter set mode screen graphically displays the PBT shift frequencies and CW pitch operations.

## AGC function

The AGC (auto gain control) controls receiver gain to produce a constant audio output level even when the received signal strength is varied by fading, etc.

The transceiver has 3 AGC characteristics (time constant; fast, mid, slow) for non-FM mode.

The FM mode AGC time constant is fixed as 'FAST' (0.1 sec.) and AGC time constant cannot be selected.

### AGC time constant selection

- ① Select non-FM mode.
- ② Push [AGC] one or more times to select AGC fast, AGC medium (MID) or AGC slow.



Medium AGC time constant



Slow AGC time constant




Fast AGC time constant

### Selectable AGC time constant (unit: sec.)

Mode	Default	Selectable AGC time constant
SSB	0.3 (FAST)	OFF, 0.1, 0.2, 0.3, 0.5, 0.8,
	2.0 (MID)	1.2, 1.6, 2.0, 2.5, 3.0, 4.0,
	6.0 (SLOW)	5.0, 6.0
CW	0.1 (FAST)	OFF, 0.1, 0.2, 0.3, 0.5, 0.8,
	0.5 (MID)	1.2, 1.6, 2.0, 2.5, 3.0, 4.0,
	1.2 (SLOW)	5.0, 6.0
RTTY	0.1 (FAST)	OFF, 0.1, 0.2, 0.3, 0.5, 0.8,
	0.5 (MID)	1.2, 1.6, 2.0, 2.5, 3.0, 4.0,
	1.2 (SLOW)	5.0, 6.0
AM	3.0 (FAST)	OFF, 0.3, 0.5, 0.8, 1.2, 1.6,
	5.0 (MID)	2.0, 2.5, 3.0, 4.0, 5.0, 6.0,
	7.0 (SLOW)	7.0, 8.0
FM	0.1 (FAST)	Fixed

### Setting the AGC time constant

- ① Select the desired mode except FM mode.
- ② Push [AGC] for 2 sec. to enter AGC set mode.



- ③ Push [AGC] one or more times to select FAST time constant.
- ④ Rotate the tuning dial to set the desired time constant for 'AGC FAST.'
  - AGC time constant can be set between 0.1 to 8.0 sec. (depends on mode) or turned OFF.
  - Push [(F-3)DEF] to select a default value.
- ⑤ Push [AGC] to select medium time constant.
- ⑥ Rotate the tuning dial to set the desired time constant for 'AGC MID.'
  - AGC time constant can be set between 0.1 to 8.0 sec. (depends on mode) or turned OFF.
  - Push [(F-3)DEF] to select a default value.
- ⑦ Push [AGC] to select slow time constant.
- ⑧ Rotate the tuning dial to set the desired time constant for 'AGC SLOW.'
  - AGC time constant can be set between 0.1 to 8.0 sec. (depends on mode) or turned OFF.
  - Push [(F-3)DEF] to select a default value.
- ⑨ Select another mode except FM. Repeat steps ③ to ⑧ if desired.
- ⑩ Push [EXIT] to exit the AGC set mode screen.




## ■ Dualwatch operation

Dualwatch monitors 2 frequencies with the same mode simultaneously.

During dualwatch, both frequencies should be on the same band, because the bandpass filter in the RF circuit is selected for the main readout frequency.

- ① Set a desired frequency.
- ② Push [DUALWATCH] for 2 sec.
  - Equalized receive frequency and “**DUAL-M**” appear in the LCD. This quick dualwatch function can be turned OFF in set mode. (p. 68)
  - Pushing [DUALWATCH] momentarily activates the dualwatch with the previously operated frequency.




- ③ Set another desired frequency using the tuning dial.
- ④ Adjust [BAL] to set a suitable signal strength balance between the main and sub readout frequencies.
  - S-meter shows the combined signal strength.
- ⑤ To transmit on the sub readout frequency, push [CHANGE] or [SPLIT].

/// RIT function can be used for the main readout only.  
 /// ΔTX function can be used for the transmit readout (main readout when the split function is OFF; sub readout when the split function is ON).

### • Scanning during dualwatch


Scanning operates only for the main readout. To operate the scan during dualwatch, scan on the main readout and use the sub readout for your QSO using both dualwatch and split frequency operation.

- ① Program the desired programmed scan edges in the same amateur band. See p. 52 for programming.
  - If you plan to operate a ΔF scan, programming the scan edges may not be necessary.
- ② Push [SPLIT] to turn the split frequency function ON.
  - “**SPLIT**” appears.




- ③ Select VFO mode for the main readout.
- ④ Set the desired operating frequency for the main readout.

- ⑤ Push [DUALWATCH] for 2 sec.
  - The main and sub readout frequencies are equalized and the dualwatch function is turned ON.



- ⑥ Push [(F-4)SCAN] to select the scan screen.
  - Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ⑦ Push [(F-1)PROG] or [(F-2)ΔF] to start the programmed scan or ΔF scan, respectively.
  - Scan activates on the main readout between the programmed scan edges or within the ΔF span.
  - Transmitting on the sub readout stops the scan.




- ⑧ To cancel the scan, push [EXIT].

## Split frequency operation


Split frequency operation allows you to transmit and receive in the same mode on two different frequencies. The split frequency operation is basically performed using 2 frequencies on the main and sub readouts.

Following is an example of setting 21.290 MHz for receiving and 21.310 MHz for transmitting.


- Set 21.290 MHz (USB) in VFO mode.



- Push [SPLIT] momentarily, then push [CHANGE] for 2 sec.
  - The quick split function is much more convenient for selecting the transmit frequency. See the next section for details.
  - The equalized transmit frequency and “SPLIT” appear on the LCD.
  - “TX” appears to show the transmit frequency’s readout.



- Rotate the tuning dial while pushing [XFC] to set the transmit frequency to 21.310 MHz.
  - The transmit frequency can be monitored while pushing [XFC] or using dualwatch.



- Now you can receive on 21.290 MHz and transmit on 21.310 MHz.

To change the transmit and receive frequencies, push [CHANGE] to exchange the main and sub readouts.

### CONVENIENT


#### DIRECT SHIFT FREQUENCY INPUT

The shift frequency can be entered directly.

- Push [F-INP].
- Enter the desired shift frequency with the digit keys.
  - 1 kHz to 1 MHz can be set.
  - When you require a minus shift direction, push [•] in advance.
- Push [SPLIT].
  - The shift frequency is input in the sub readout and the split function is turned ON.

### EXAMPLE

To operate on 1 kHz higher frequency:



To operate on 3 kHz lower frequency:



### CONVENIENT

#### DUALWATCH FUNCTION

The dualwatch function is convenient for tuning the transmit frequency while monitoring both frequencies used for transmitting and receiving.

### CONVENIENT

#### SPLIT LOCK FUNCTION

Accidentally releasing the [XFC] switch while rotating the tuning dial changes the receive frequency. To prevent this, use both the split lock and dial lock functions to change the transmit frequency only. The split lock function cancels the dial lock function while pushing [XFC] during split frequency operation.

The dial lock’s effectiveness during split frequency operation can be selected in the set mode for both receive and transmit frequencies; or only the receive frequency. (p. 69)

## ■ Quick split function


When you find a DX station, an important consideration is how to set the split frequency.

When you push the [SPLIT] switch for 2 sec., split frequency operation is turned ON, the sub readout is equalized to the main readout frequency and enters standby for transmit frequency input.


This shortens the time needed to start split frequency operation.

The quick split function is ON by default. For your convenience, it can be turned OFF in set mode. (p. 68) In this case, the [SPLIT] switch does not equalize the main and sub readout frequencies.


- ① Suppose you are operating at 21.290 MHz (USB) in VFO mode.



- ② Push [SPLIT] for 2 sec.
- Split frequency operation is turned ON.
  - The sub readout is equalized to the main readout frequency.
  - The sub readout enters standby for transmit frequency input.



- ③ Rotate the tuning dial to set the transmit frequency; or, input the transmit frequency using the keypad and [ENT]; or, input a shift frequency using the keypad and [SPLIT].
- The transmit frequency can be monitored while pushing [XFC] or using dualwatch.



### PRACTICAL EXAMPLE

When you are searching for DX stations and you suspect that a DX station may say “up ‘X’ kHz” for their receive frequency:

#### OPERATION 1

- ① Push [SPLIT] for 2 sec. to standby for split operation.
- ② If the DX station says “up 10 kHz”:
- Push [1], [0] then [SPLIT].
  - Or, rotate the tuning dial.

#### OPERATION 2

If the DX station says “down 5 kHz” before you enter standby for split operation:

- ➡ Push [F-INP], [•], [5] then [SPLIT].
- The split function is turned ON and “5 kHz down” frequency is entered in the sub readout.

### PRACTICAL EXAMPLE

When you receive a pile-up and you want to start split frequency operation to simplify picking out stations:

- ① Push [SPLIT] momentarily and push [CHANGE] for 2 sec.
- The sub readout frequency is equalized to the main readout frequency and “SPLIT” appears.
- ② Rotate the tuning dial to set your receive frequency in the main readout.
- ③ Announce your receive frequency.
- ④ After you catch one of the calling stations’ call signs, push and hold the PTT switch to respond.
- While pushing [XFC], you can monitor your transmit frequency.


## RIT and ΔTX

### •RIT function


The RIT function shifts the receive frequency up to ±9.999 kHz in 1 Hz steps (10 Hz steps when cancelling the 1 Hz step readout) without moving the transmit frequency.

•See 30 on p. 6 for function description.


① Push the [RIT] switch.



② Rotate the [RIT/ΔTX] control.



③ To reset the RIT frequency, push [CLEAR] for 2 sec.



④ To cancel the RIT function, push [RIT] again.


•“RIT” disappears.

### •ΔTX function


The ΔTX function shifts the transmit frequency up to ±9.999 kHz in 1 Hz steps (10 Hz steps when cancelling the 1 Hz step readout) without moving the receive frequency.

•See 31 on p. 6 for function description.


① Push the [ΔTX] switch.



② Rotate the [RIT/ΔTX] control.



③ To reset the ΔTX frequency, push [CLEAR] for 2 sec.



④ To cancel the ΔTX function, push [ΔTX] again.


•“ΔTX” disappears.

When RIT and ΔTX are ON at the same time, the [RIT/ΔTX] control shifts both the transmit and receive frequencies from the displayed frequency at the same time.

### •Calculate function

The shift frequency of the RIT or ΔTX function can be added/subtracted to the displayed frequency.

While displaying the RIT and/or ΔTX shift frequency, push [RIT] or [ΔTX] for 2 sec.



### •Practical example

When you find a DX station on 21.025 MHz/CW and the station is picking up stations transmitting slightly up from 21.025 MHz.



- ① Push [RIT] and [ΔTX] to turn both the RIT and ΔTX functions ON.
- ② Rotate [RIT/ΔTX] to find the DX station's receive frequency.
- ③ When you find the DX station's receive frequency, push [RIT] to turn the RIT function OFF.
  - Now you can transmit the DX station's receive frequency and receive the DX station's transmit frequency (21.025 MHz).
- ④ Start transmitting while the station is standing by.

## ■ Monitor function

The monitor function allows you to monitor your transmit IF signals in any mode through the speaker. Use this to check voice characteristics while adjusting SSB transmit tones. (p. 65) The CW sidetone functions regardless of the [MONITOR] switch setting.

- ① Push [MONITOR].
  - The indicator lights when the monitor function is ON.
- ② Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ③ Push [(F-5)SET] then [(F-1)LEVEL] to enter level set mode.
- ④ Push [(F-1)▲] or [(F-2)▼] to select the monitor level item.
- ⑤ Adjust monitor gain using the tuning dial.
  - Pushing [(F-3)DEF] sets the selected item to the default value of the item.
- ⑥ Push [EXIT] twice to exit level set mode.

- Use headphones to prevent feedback.
- Set the transmit tone settings to the 0 dB positions to check the unaltered characteristics of transmitter or microphone.



## ■ VOX function

The VOX (Voice-Operated Transmission) function toggles between transmit and receive with your voice. This function provides an opportunity to input log entries into your computer, etc., while operating.



### •Using the VOX function

- ① Select a phone mode (SSB, AM, FM).
- ② Push [VOX] to turn the VOX function ON or OFF.

### •Adjusting the VOX function

- ① Select a phone mode (SSB, AM, FM).
- ② Push [VOX] to turn VOX function ON.
- ③ Push [VOX] for 2 sec. to enter VOX set mode.
- ④ Select the VOX gain item using [F-1] or [F-2].
- ⑤ While speaking into the microphone, rotate the tuning dial to the point where the transceiver is continuously transmitting.
- ⑥ Adjust the VOX delay for a convenient interval before returning to receive.
  - Select the VOX delay item using [F-1] or [F-2].
  - Rotate the tuning dial.
- ⑦ If the receive audio from the speaker toggles to transmit, adjust the anti VOX to the point where it has no effect.

[VOX] switch in phone modes




## Meter function

The transceiver has 4 transmit meter functions for your convenience. Select the desired meter with the [METER] switch.

### Analog transmit meter

➔ Push [METER] to select RF power (Po), SWR, ALC or compression level (COMP) for transmit metering.




DISPLAY INDICATION	MEASUREMENT
Po	Indicates the relative RF output power in %.
SWR	Indicates the SWR over the transmission line.
ALC	Indicates the ALC level. When the meter movement shows the input signal level exceeds the allowable level, the ALC limits the RF power. In such cases, reduce the [MIC GAIN] control.
COMP	Indicates the compression level when the speech compressor is in use.

In addition, the transceiver can display the multi-function digital meter in the LCD display, which displays all transmit meters simultaneously.

### Multi-function digital meter


- ① Push [METER] for 2 sec. to turn the multi-function digital meter ON or OFF.
- ② Push [(F-1)P-HOLD] to toggle the peak level hold function ON or OFF.
  - “P-HOLD” appears on the window title when the peak level hold function is turned ON.



## SWR reading

The SWR meter indicates the SWR over the transmission line in all modes.

- ① Push [TUNER] to turn the antenna tuner OFF.
- ② Push [METER] one or more times to select the Po meter.
- ③ Push [CW/RTTY] once or twice to select RTTY mode.
- ④ Push [TRANSMIT].
- ⑤ Rotate [RF POWER] clockwise past the 12 o'clock position for more than 30 W output power (30%).
- ⑥ Push [METER] once to select the SWR meter as the transmit meter.
- ⑦ Read the SWR on the SWR meter.



▨ The built-in antenna tuner matches the transmitter to the antenna when the SWR is lower than 3:1.

## ■ Speech compressor

The RF speech compressor increases average RF output power, improving signal strength and readability in SSB.


### •Speech compressor

- ① Select USB or LSB mode.
- ② Push [COMP] momentarily to turn the speech compressor ON and OFF.
- ③ Push [COMP] for 2 sec. to toggle between narrow, middle or wide transmit filter.
  - Transmit filter width:
  - NAR 2.0 kHz
  - MID 2.6 kHz
  - WIDE 2.9 kHz


### •Compression level setting

- ① Select USB or LSB mode.
- ② Preset the transceiver as follows:
  - [COMP] function : OFF
  - [METER] function : ALC
  - [MIC GAIN] control : Center position
  - [COMP] control : Center position
  - [RF POWER] control : Max. counterclockwise
- ③ Transmit at your normal voice level.
- ④ Adjust the [MIC GAIN] control so that the ALC meter reads within the ALC zone, whether or not you speak softly or loudly.
- ⑤ Push [COMP] momentarily to turn the speech compressor ON.

- ⑥ Push [METER] once to select the COMP meter.
- ⑦ Adjust the [COMP] control so that the COMP meter reads within 10 dB and 20 dB.



When the ALC meter peaks above the ALC zone, your transmitted voice may be distorted.




## Digital voice recorder

The transceiver has a total of 8 memory channels, 4 each for transmit and receive, of digital voice memories. A maximum message of 15 sec. can be recorded in each transmit and receive channels.


Providing a transmission memory is very convenient for repeated CQ and number transmissions at contest times, as well as when making consecutive calls in DX'pedition.

### Recording a received audio


- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select a phone mode by pushing [SSB] or [AM/FM].
- ③ Push [(F-2)VOICE] to call up the voice recorder screen.



- ④ Push [(F-1)PLAY] to select the voice memory screen.
  - If the transmit voice memory channel (T1–T4) appears, push [(F-5)T/R] to select receive voice memory channel.




- ⑤ Push the desired memory channel, [(F-1)R1]–[(F-4)R4], for 2 sec. to start recording.
  - The operating frequency, mode and current time are programmed automatically.
  - Previously recorded contents are cleared.




- ⑥ Push the selected memory channel, [(F-1)R1]–[(F-4)R4], again to stop recording.
  - Recording is automatically terminated after 15 sec.
- ⑦ Push [EXIT] twice to exit voice memory screen.

### Playing the recorded audio

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select a phone mode by pushing [SSB] or [AM/FM].
- ③ Push [(F-2)VOICE] to call up the voice recorder screen.
- ④ Push [(F-1)PLAY] to select the voice memory screen.
  - If the transmit voice memory channel (T1–T4) appears, push [(F-5)T/R] to select receive voice memory channel.



- ⑤ Push the desired memory channel, [(F-1)R1]–[(F-4)R4], momentarily to playback.



- ⑥ Push the selected memory channel, [(F-1)R1]–[(F-4)R4], again to stop playback if desired.
- ⑦ Push [EXIT] twice to exit voice memory screen.




## ■ Digital voice recorder (continued)


### •Recording a message for transmit

To transmit a message using a voice recorder, record the desired message in advance as described below.


- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select a phone mode by pushing [SSB] or [AM/FM].
- ③ Push [(F-2)VOICE] to call up the voice recorder screen.



- ④ Push [(F-2)MIC REC] to select the voice memory recording screen.



- ⑤ Push the desired memory channel, [(F-1)T1]–[(F-4)T4], for 2 sec. to start recording.
  - Speak into the microphone without pushing the [PTT] switch.
  - Previously recorded contents are cleared.




- ⑥ Adjust the [MIC GAIN] control so that the [MIC REC LEVEL] indicator reads within 100%.
- ⑦ Push the selected memory channel, [(F-1)T1]–[(F-4)T4], again to stop recording.
  - Recording is automatically terminated after 15 sec.
- ⑧ Push [EXIT] twice to exit voice memory screen.

### •Confirming a message for transmit

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select a phone mode by pushing [SSB] or [AM/FM].
- ③ Push [(F-2)VOICE] to call up the voice recorder screen.
- ④ Push [(F-2)MIC REC] to select the voice memory recording screen.

- ⑤ Push the desired memory channel, [(F-1)T1]–[(F-4)T4], momentarily to start playback and confirmation.




- ⑥ Push the selected memory channel, [(F-1)T1]–[(F-4)T4], again to stop playback if desired.
- ⑦ Push [EXIT] twice to exit voice memory screen.

### •Programming a memory name for transmit

Memory channels can be tagged with alphanumeric names of up to 20 characters each.

Capital letters, small letters, numerals, some symbols (! # \$ % & ¥ ? " ' ` ^ + - \* / · · · ; = < > ( ) [ ] { } | \_ ~) and spaces can be used.

- ① Record a message as described above.
- ② Call up the voice memory recording screen as described in step ① to ④ above.
- ③ Push [(F-5)NAME] to enter memory name edit condition.
  - A cursor appears and blinks.
- ④ Push [(F-5)T1..T4] one or more times to select the desired voice memory.




- ⑤ Input the desired character by rotating the tuning dial or by pushing the band key for number input.
  - Push [ABC] or [abc] to toggle capital and small letters.
  - Push [123] or [etc] to toggle numerals and symbols.
  - Push [(F-1)◀] or [(F-2)▶] for cursor movement.
  - Push [(F-3)DEL] to delete the selected character.
  - Push [(F-4)SPACE] to input a space.
- ⑥ Push [EXIT] to input and set the name.
  - The cursor disappears.
- ⑦ Repeat steps ④ to ⑥ to program another voice memory's name, if desired.
- ⑧ Push [EXIT] twice to exit voice memory screen.


## ■ Digital voice recorder (continued)

### • Sending a message for transmit

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select a phone mode by pushing [SSB] or [AM/FM].
- ③ Push [(F-2)VOICE] to call up the voice recorder screen.
- ④ Push [(F-1)PLAY] to select the voice memory screen.
  - If the receive voice memory channel (R1–R4) appears, push [(F-5)T/R] to select transmit voice memory channel.



- ⑤ Push the desired memory channel, [(F-1)T1]–[(F-4)T4], momentarily to transmit the contents.




- ⑥ Push the selected memory channel, [(F-1)T1]–[(F-4)T4], again to stop, if desired.
- ⑦ Push [EXIT] twice to exit voice memory screen.

### • Transmit monitor function

The monitor function can be automatically turned ON while transmitting a voice memory message.


- ① Call up the voice recorder screen as described above.
- ② Push [(F-5)SET] to select the voice memory set mode screen.
- ③ Rotate the tuning dial to turn the monitor function ON and OFF.
  - Push [(F-3)DEF] to select the default condition.




- ④ Push [EXIT] to return to the voice recorder screen.

### • Transmit level setting

- ① Call up the voice recorder screen as described at left.
- ② Push [(F-3)TX LEV.] to select the voice memory transmit level set mode screen.



- ③ Push the desired memory channel, [(F-1)T1]–[(F-4)T4], momentarily to transmit the contents.
- ④ Rotate the tuning dial to adjust the transmit voice level.
  - Push [(F-5)DEF] to select the default condition.




- ⑤ Push [EXIT] to return to the voice recorder screen.

## ■ RTTY decoder


The transceiver has an RTTY decoder for Baudot (mark freq.: 2125 Hz, shift freq.: 170 Hz, 45 bps).

An external terminal unit (TU) or terminal node controller (TNC) is not necessary for receiving a Baudot signal.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [CW/RTTY] once or twice to select RTTY mode.
- ③ Push [(F-2)DECODE] to turn the RTTY decoder ON.
  - RTTY decoder screen appears.



- ④ If the RTTY filter is turned OFF, push [RTTY FIL] to turn the function ON.
  - The RTTY decoder does not function when the RTTY filter is turned OFF.
- ⑤ Push [(F-1)HOLD] to freeze the current screen.
  - “HOLD” appears while the function is in use.
- ⑥ Push [(F-5)WIDE] to toggle the normal or wide screen space.




- ⑦ Push [(F-2)CLR] for 2 sec. to clear the displayed characters.
- ⑧ Push [EXIT] to exit the RTTY decoder screen.

### •Setting the decoder threshold level

Adjust the RTTY decoder threshold level if some characters are displayed when no signal is received.

- ① Call up the RTTY decoder screen as described at left.
- ② Push [(F-4)ADJ] to select the threshold level setting condition.
- ③ Rotate the tuning dial to adjust the RTTY decoder threshold level.
  - Push [(F-3)DEF] to select the default condition.



- ④ Push [EXIT] to return to the RTTY decoder screen.


▨ The UnShift On Space (USOS) function and new line code can be set in the miscellaneous (others) set mode. (pgs. 70, 71)

## ■ RTTY tuning meter

The transceiver has an RTTY tuning indicator to be tuned correctly and easily.

The RTTY tuning meter is automatically displayed when the RTTY filter is turned ON.

- ① Push [CW/RTTY] once or twice to select RTTY mode.
- ② Push [RTTY FIL] to activate the RTTY filter and RTTY tuning meter.




## Electronic CW keyer

The transceiver has an electronic keyer. Keying speed can be adjusted with [KEY SPEED]. Keying weight, the ratio of dot:space:dash, can be set from 1:1:2.8 to 1:1:4.5 in keyer set mode.


### Setting the electronic keyer

- Push [CW/RTTY] once or twice to select CW mode.



[KEYER] switch [CW/RTTY] switch

- Push [KEYER] to select keyer set mode.



- Push [(F-4)CW KEY] to select memory keyer set mode.

- Select the "Keyer Repeat Time" item using [F-1].



- Rotate the tuning dial to select the memory keyer repeat interval. See the next page for details.
  - 1, 2, 3, 10 or 30 sec. can be set.
  - Push [(F-3)DEF] to select a default interval of 2 sec.

- Push [F-2] to select the "Dot/Dash Ratio" item.



- Rotate the tuning dial to select the keying weight.

- 1:1:2.8 to 1:1:4.5 can be set.
- Check the ratio with side tone in CW mode.
- Push [(F-3)DEF] to select a default ratio of 1:1:3.0.

- Push [F-2] to select the "Rise Time" item.



- Rotate the tuning dial to select the time which the output power becomes the set transmit power.

- Push [F-2] to select the "Paddle Polarity" item.



- Rotate the tuning dial to select the paddle polarity between normal and reverse polarity.

- Push [F-2] to select the "Keyer Type" item.

- Rotate the tuning dial to set the electronic keyer function to electronic keyer, bug-key or straight key (electronic keyer OFF).

- Bug-key setting can be substituted for a bug-key while operating with a paddle. Set to "Straight" for a real bug-key, or connect the bug-key to [KEY] on the rear panel.




- Push [F-2] to select the "Mic Up/Down Keyer" item.

- Rotate the tuning dial to turn the substitute paddle function ON or OFF.

- The up/down keys of the microphone can be substituted for a paddle. When ON is selected, they do not function as up/down keys in all modes.

- Push [EXIT] to exit keyer set mode.

### KEYING WEIGHT EXAMPLE: Morse code "K"




\*SPACE and DOT length can be adjusted with [KEY SPEED] only.

## ■ Memory keyer

The memory keyer memorizes and can re-transmit 4 CW key codes for often-used CW sentences, antenna types, etc. Total capacity of the memory keyer is 54 characters in each memory channel.

### • Programming the memory keyer

- ① Push [CW/RTTY] to select CW mode.
- ② Push [(F-2)KEYER] to select keyer set mode.
- ③ Push [(F-2)EDIT] to enter the memory keyer edit screen.



- ④ Push [M1..M4] one or more times to select the desired keyer memory channel.
- ⑤ Select the desired character group by pushing the character group keys ([ABC], [123], [etc]) one or more times.
- ⑥ Select the desired character by rotating the tuning dial or by pushing the band key for number input.
  - Push [(F-1)◀] or [(F-2)▶] for cursor movement.
  - Push [(F-3)DEL] to delete the selected character.
  - Push [(F-4)SPACE] to input a space.
  - “\*” is for contact numbers and can be input for the count up trigger channel (“ ” appears).
- ⑦ Repeat step ⑥ until the desired contents are input.
- ⑧ Push [M1..M4] to select the next memory channel and repeat step ⑥ for character input, if desired.
- ⑨ Push [EXIT] to exit the memory keyer edit screen.

### • Transmitting memory keyer contents

- ① Push [CW/RTTY] to select CW mode.
- ② Push [KEYER] to select keyer set mode.
- ③ Push [(F-1)SEND] to enter the memory keyer screen.



- ④ Push [(F-1)M1] – [(F-4)M4] momentarily to transmit the contents one time; push these keys for 2 sec. to transmit the contents repeatedly.
  - “M1”–“M4” are highlighted while transmitting.
  - “ ” appears while transmitting repeatedly.
  - Set the repeat interval of the memory keyer to 1, 2, 3, 10 or 30 sec. See the previous page for keyer set mode.
  - To count down the contact number, push [(F-5)–1].
- ⑤ Push [EXIT] to exit memory keyer screen.

### • Setting the contact (serial) number

Contact number can be automatically transmitted from one of the memory keyer channels. The Morse cut numbers can be used as the contact numbers. The maximum number for contact numbers is 9999.

- ① Push [CW/RTTY] to select CW mode.
- ② Push [KEYER] to select keyer set mode.
- ③ Push [(F-3)001] to enter contact number screen.



- ④ Rotate the tuning dial to select the cut number type, if desired.
  - “Normal” does not use Morse cut numbers.
  - “190 → ANO” sets 1 as A, 9 as N and Ø as O.
  - “190 → ANT” sets 1 as A, 9 as N and Ø as T.
  - “90 → NO” sets 9 as N and Ø as O.
  - “90 → NT” sets 9 as N and Ø as T.
- ⑤ Push [F-2] to select the “Count Up Trigger” item.



- ⑥ Rotate the tuning dial to select the desired memory channel for contest numbers.
- ⑦ Push [F-2] to select the “Present Number” item.




- ⑧ Push [(F-3)001CLR] for 2 sec. to clear the contact number.
- ⑨ Push [EXIT] to exit keyer set mode.


## ■ Spectrum scope screen

This function allows you to display the relative strengths of signals around the center frequency. The span can be set to  $\pm 12.5$  kHz,  $\pm 25$  kHz,  $\pm 50$  kHz and  $\pm 100$  kHz. Ideal for monitoring band conditions in an instant.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-1)SCOPE] to select the scope screen.



- ③ Push [(F-1)SPAN] one or more times to select the scope span.
- ④ Push [(F-2)ATT] one or more times to activate an attenuator or turn the attenuator OFF.
  - 10, 20 and 30 dB attenuators are available.
- ⑤ Push [(F-3)MARKER] one or more times to select the marker (sub readout or transmit frequency) or turn the marker OFF.
  - “TX MARKER” displays the marker at the transmit frequency.
  - “SUB MARKER” displays the marker at the sub readout frequency.



Appears when the marker is out of range.      Sub readout or TX marker      Appears when the marker is out of range.


- ⑥ Push [(F-4)HOLD] to freeze the current spectrum waveform.
  - “HOLD” appears while the function is in use.
- ⑦ Push [EXIT] to exit the scope screen.

### • Spectrum scope during transmitting

The spectrum scope shows the transmit signal waveform while transmitting. This can be deactivated if desired.

When “OFF” is selected, the spectrum scope holds the received waveform while transmitting and does not show the transmit waveform.

- ① Call up the scope screen as described at left.
- ② Push [(F-5)SET] to select the spectrum scope set mode.
- ③ Push [F-1] to select the “Scope during Tx” item.
- ④ Rotate the tuning dial to display the spectrum scope while transmitting or not.




- ⑤ Push [EXIT] to exit keyer set mode.

### • Maximum level hold function

The spectrum scope shows the peak level holding function. Peak levels are displayed in the background of the current spectrum in a different color until the receive frequency changes. This can be deactivated if desired.

- ① Call up the scope screen as described at left.
- ② Push [(F-5)SET] to select the spectrum scope set mode.
- ③ Push [F-2] to select the “Max Hold” item.
- ④ Rotate the tuning dial to turn the peak level holding function ON or OFF.




- ⑤ Push [EXIT] to exit keyer set mode.

▨ If a strong signal is received, ghost waveform may appear. Push [(F-2)ATT] one or more times to activate the spectrum scope attenuator in this case.

## ■ Automatic antenna selection

The transceiver covers 0.1–60 MHz over 10 bands. Each band key has a band memory which can memorize a selected antenna (ANT1, ANT2, ANT1/RX antenna and ANT2/RX antenna). When you change the operating frequency beyond a band, the previously used antenna is automatically selected for the new band. This function is convenient when you use 2 or 3 antennas.

To use the band memory, enter set mode and confirm that "Auto" is selected as the [ANT] switch item. (p. 70)



- When OFF is selected, the [ANT] switch does not function and [ANT1] is always selected.
- When "Manual" is selected, the [ANT] switch functions, however, band memory does not function. In this case, you must select an antenna manually.
- When "Auto" is selected (default setting), the antenna tuner ON/OFF condition is also memorized in the band memory.
- When "Auto" or "Manual" is selected, the antenna tuner ON/OFF condition is consistent with the [ANT] switch.

### • Antenna switch selection example

Under the following condition, "Auto" should be selected as the [ANT] switch set mode item.

- When you use 2 antennas.


Under the following conditions, "Manual" should be selected as the [ANT] switch set mode item.

- When using 1 antenna.
- When using the EX-627 HF AUTOMATIC ANTENNA SELECTOR for more than 3 antennas (except for receive antenna).
- When using an external antenna tuner.

## ■ Dial lock function

The dial lock function prevents changes by accidental movement of the tuning dial. The lock function electronically locks the dial.

- ➔ Push [LOCK] to toggle the dial lock function ON and OFF.
  - The [LOCK] indicator lights when the dial lock function is in use.




## Repeater operation


A repeater amplifies received signals and retransmits them at a different frequency. When using a repeater, the transmit frequency is shifted from the receive frequency by an offset frequency. A repeater can be accessed using split frequency operation with the shift frequency set to the repeater's offset frequency.

For accessing a repeater which requires a repeater tone, set the repeater tone frequency in set mode as described below.


- ① Set the offset frequencies (HF, 50 MHz) and turn ON the quick split function in set mode (others) in advance. (pgs. 68, 69)
- ② Push [VFO/MEMO] to select VFO mode.



- ③ Push the desired band key.
- ④ Push [AM/FM] one or more times to select FM mode.
- ⑤ Set the receive frequency (repeater output frequency).



- ⑥ Push [SPLIT] for 2 sec. to start repeater operation.
  - Repeater tone is turned ON automatically.
  - Shifted transmit frequency and "TX" appear in the sub readout.
  - The transmit frequency can be monitored while pushing [XFC] or using dualwatch.



Shifted frequency appears. Tone encoder is automatically turned ON.


- ⑦ Push and hold [PTT] to transmit; release [PTT] to receive.
- ⑧ To return to simplex, push [SPLIT] momentarily to clear the sub display.

### Setting the repeater tone

Some repeaters require subaudible tones to be accessed. Subaudible tones are superimposed over your normal signal and must be set in advance. The transceiver has 50 tones from 67.0 Hz to 254.1 Hz.

Each memory channel can store an independent setting.

- ① Select FM mode.
- ② Push [TONE] for 2 sec. to enter tone set mode.
- ③ Push [F-1] to select the repeater tone item.
- ④ Rotate the tuning dial to select the desired repeater tone frequency.



- ⑤ Push [EXIT] to exit tone set mode.

### Available repeater tones (Unit: Hz)

67.0	85.4	107.2	136.5	165.5	186.2	210.7	254.1
69.3	88.5	110.9	141.3	167.9	189.9	218.1	
71.9	91.5	114.8	146.2	171.3	192.8	225.7	
74.4	94.8	118.8	151.4	173.8	196.6	229.1	
77.0	97.4	123.0	156.7	177.3	199.5	233.6	
79.7	100.0	127.3	159.8	179.9	203.5	241.8	
82.5	103.5	131.8	162.2	183.5	206.5	250.3	

### CONVENIENT


Store repeater tone frequencies and ON/OFF settings in memory channels for easy recall.




## ■ Tone squelch operation

The tone squelch opens only when receiving a signal containing a matching subaudible tone. You can silently wait for calls from group members using the same tone.

- ① Push [VFO/MEMO] to select VFO mode.



- ② Push the desired band key.  
 ③ Push [AM/FM] one or more times to select FM mode.  
 ④ Push [TONE] one or more times until "TSQL" appears in the function display.




- ⑤ When the received signal includes a matching tone, squelch opens and the signal can be heard.  
 • When the received signal's tone does not match, tone squelch does not open, however, the S-indicator shows signal strength.  
 • To open the squelch manually, push [XFC].  
 ⑥ Operate the transceiver in the normal way.  
 ⑦ To cancel the tone squelch, push [TONE] to clear "TSQL."

### • Setting the tone squelch tone

The transceiver has 50 tones from 67.0 Hz to 254.1 Hz.

- ① Select FM mode.  
 ② Push [TONE] for 2 sec. to enter tone set mode.  
 ③ Push [F-2] to select the tone squelch tone item.  
 ④ Rotate the tuning dial to select the desired tone squelch frequency.



- ⑤ Push [EXIT] to exit tone set mode.

### Available tone squelch tones (Unit: Hz)

67.0	85.4	107.2	136.5	165.5	186.2	210.7	254.1
69.3	88.5	110.9	141.3	167.9	189.9	218.1	
71.9	91.5	114.8	146.2	171.3	192.8	225.7	
74.4	94.8	118.8	151.4	173.8	196.6	229.1	
77.0	97.4	123.0	156.7	177.3	199.5	233.6	
79.7	100.0	127.3	159.8	179.9	203.5	241.8	
82.5	103.5	131.8	162.2	183.5	206.5	250.3	

### CONVENIENT

Store tone squelch frequencies and ON/OFF settings in memory channels for easy recall.

## ■ Antenna tuner operation


The internal automatic antenna tuner matches the transceiver to the connected antenna automatically. Once the tuner matches an antenna, the variable capacitor angles are memorized as a preset point for each frequency range (100 kHz steps). Therefore, when you change the frequency range, the variable capacitors are automatically preset to the memorized point.

**CAUTION: NEVER** transmit with the tuner ON when no antenna is connected. This will damage the transceiver. Be careful of the antenna selection.

### TUNER OPERATION

- ➔ Push the [TUNER] switch to turn the internal antenna tuner ON. The antenna is tuned automatically when the antenna SWR is higher than 1.5:1.
  - When the tuner is ON, the [TUNER] switch lights.

[TUNER] switch




### MANUAL TUNING

During SSB operation at low voice levels, the internal tuner may not be tuned correctly. In such cases, manual tuning is helpful.

- ➔ Push [TUNER] for 2 sec., to start manual tuning.
  - A side tone is emitted and [TUNER] blinks while tuning.
  - If the tuner cannot reduce the SWR to less than 1.5:1 after 20 sec. of tuning, the [TUNER] switch indicator goes out.

Push [TUNER] for 2 sec.



### AUTOMATIC TUNER START (HF bands only)

If you want to deactivate the tuner under conditions of VSWR 1.5:1 or less, use the auto tuner start function and turn the tuner OFF. This function activates the tuner automatically when the SWR exceeds 1.5:1.

This function is turned ON in set mode. (p. 69).

### PTT TUNER START

The tuner is always tuned when the PTT is pushed after the frequency is changed (more than 1% from last-tuned frequency). This function removes the "push and hold [TUNER]" operation and activates for the first transmission on a new frequency.

This function is turned ON in set mode. (p. 69).

## NOTES:

### •If the tuner cannot tune the antenna

Check the following and try again:

- the [ANT] connector selection.
- the antenna connection and feedline.
- the unaltered antenna SWR. (Less than 3:1 for HF bands; Less than 2.5:1 for 50 MHz band)
- the transmit power. (8 W for HF bands; 15 W for 50 MHz band)
- the power source voltage/capacity.

If the tuner cannot reduce the SWR to less than 1.5:1 after checking the above, perform the following:

- repeat manual tuning several times.
- tune with a 50 Ω dummy load and re-tune the antenna.
- turn power OFF and ON.
- adjust the antenna cable length. (This is effective for higher frequencies in some cases.)

### •Tuning a narrow bandwidth antenna

Some antennas, especially for low bands, have a narrow bandwidth. These antennas may not be tuned at the edge of their bandwidth, therefore, tune such an antenna as follows:

Suppose you have an antenna which has an SWR of 1.5:1 at 3.55 MHz and an SWR of 3:1 at 3.8 MHz.

- ① Push [TUNER] to turn the antenna tuner ON.
- ② Select CW mode.
- ③ Turn OFF the break-in function. (p. 5)
- ④ Push [TRANSMIT] to set to the transmit condition.
- ⑤ Set 3.55 MHz and key down.
- ⑥ Set 3.80 MHz and key down.
- ⑦ Push [TRANSMIT] to return to the receive condition.

## ■ Optional external tuner operation


### • AH-4/AH-3 HF AUTOMATIC ANTENNA TUNER

The AH-4/AH-3 matches the IC-756PRO to a long wire antenna more than 3 m/10 ft long (3.5 MHz and above) or more than 12 m/40 ft long (1.8 MHz and above).


- See p. 20 for the transceiver and AH-4/AH-3 connection.
- See the AH-4/AH-3 instruction manual for AH-4/AH-3 installation and antenna connection details.

#### AH-4/AH-3 setting example:

For mobile operation



For outdoor operation



#### ⚠ WARNING: HIGH VOLTAGE!

**NEVER** touch the antenna element while tuning or transmitting.

**NEVER** operate the AH-4/AH-3 without an antenna wire. The tuner and transceiver will be damaged.

**NEVER** operate the AH-4/AH-3 when it is not grounded.

Transmitting before tuning may damage the transceiver. Note that the AH-4/AH-3 cannot tune when using a  $\frac{1}{2} \lambda$  long wire or multiple of the operating frequency.


- When connecting the AH-4/AH-3, the antenna connector assignments are [ANT2] for the internal tuner and [ANT1] for the AH-4/AH-3. The antenna indicator in the LCD displays "ANT1(EXT)" when the AH-4/AH-3 is connected and selected.
- The AH-3 can be used for HF bands only. It cannot be used for the 50 MHz band.

### • AH-4/AH-3 operation

Tuning is required for each frequency. **Be sure** to re-tune the antenna before transmitting when you change the frequency—even slightly.

- ① Set the desired frequency in an HF or 50 MHz band for using with the AH-4. Set the desired frequency in an HF band for using with the AH-3.
  - The AH-4/AH-3 will not operate on frequencies outside of ham bands.
- ② Push [TUNER] for 2 sec.
  - The [TUNER] light blinks while tuning.

[TUNER] switch



- ③ The [TUNER] light lights constantly when tuning is complete.
  - When the connected wire cannot be tuned, the [TUNER] light goes out, the AH-4/AH-3 is bypassed and the antenna wire is connected to the antenna connector on the transceiver directly.
- ④ To bypass the AH-4/AH-3 manually, push [TUNER].

### • ANTENNA TUNER OF THE IC-PW1, IC-4KL or IC-2KL/IC-AT500

When using an external antenna tuner such as the IC-PW1's tuner, IC-4KL's tuner or IC-AT500 with a linear amplifier, tune with the external antenna tuner, while the internal tuner is turned OFF. After tuning is completed, turn the internal tuner ON. Otherwise, both tuners tune simultaneously and correct tuning may not be obtained.

See the instruction manual included with each antenna tuner for their respective operations.

## Memory channels

The transceiver has 101 memory channels. The memory mode is very useful for quickly changing to often-used frequencies.


All 101 memory channels are tuneable which means the programmed frequency can be tuned temporarily with the tuning dial, etc. in memory mode.

MEMORY CHANNEL	MEMORY CHANNEL NUMBER	CAPABILITY	TRANSFER TO VFO	OVER-WRITING	CLEAR
Regular memory channels	1–99	One frequency and one mode in each memory channel.	Yes	Yes	Yes
Scan edge memory channels	P1, P2	One frequency and one mode in each memory channel as scan edges for programmed scan.	Yes	Yes	No

## Memory channel selection


### •Using the [▲] or [▼] keys

- Push [VFO/MEMO] to select memory mode.
- Push [▲]/[▼] several times to select the desired memory channel.
  - Push and hold [▲]/[▼] for continuous selection.
  - [UP] and [DN] on the microphone can also be used.
- To return to VFO mode, push [VFO/MEMO] again.



### •Using the keypad

- Push [VFO/MEMO] to select memory mode.
- Push [F-INP].
- Push the desired memory channel number using the keypad.
  - Enter 100 or 101 to select scan edge channel P1 or P2, respectively.
- Push [▲] or [▼] to select the desired memory channel.




## ■ Memory channel screen

The memory channel screen simultaneously shows 7 memory channels and their programmed contents. 13 memory channels can be displayed in the wide memory channel screen.

You can select a desired memory channel from the memory channel screen.

### •Selecting a memory channel using the memory channel screen


- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-3)MEMORY] to select the memory channel screen.
  - [(F-5)WIDE] toggles the standard and wide screens.



- ③ Rotate the tuning dial while pushing [(F-2)SET] to select the desired memory channel.
  - [▲] and [▼] can also be used.
- ④ Push [EXIT] to exit the memory channel screen.

### •Confirming programmed memory channels

- ① Select the memory channel screen as described above.
- ② Rotate the tuning dial while pushing [(F-1)ROLL] to scroll the screen.
- ③ Push [(F-2)SET] to select the highlighted memory channel, if desired.




“▶” appears when the memory channel is selected.

- ④ Push [EXIT] to exit the memory channel screen.

### •Setting a memory channel as a select memory

Select memory channels are used for select memory scan. Select memory scan repeatedly scans the select memory channels only. This is useful to speedup the memory scan interval. Of course, select memory channels are also scanned during normal memory scan.

- ① Select the memory channel screen as described at left.
- ② Rotate the tuning dial while pushing [(F-2)SET] to select the desired memory channel.
  - [▲] and [▼] can also be used.
- ③ Push [(F-3)SELECT] to set the memory channel as a select memory or not.



“★” appears for select memory channel.

- ④ Repeat steps ② to ③ to program another memory channel as a select memory channel, if desired.
- ⑤ Push [EXIT] to exit the memory channel screen.

Setting select memory channels is also possible in the scan screen.


## Memory channel programming

Memory channel programming can be performed either in VFO mode or in memory mode.

### •Programming in VFO mode

- ① Set the desired frequency and operating mode in VFO mode.
- ② Push [▲]/[▼] several times to select the desired memory channel.
  - Memory channel screen is convenient for selecting the desired channel.
  - Memory channel contents appear in the memory channel readout (below the frequency readout).
  - “--.--.--” appears if the selected memory channel is a blank channel (and does not have contents).
- ③ Push [MW] for 2 sec. to program the displayed frequency and operating mode into the memory channel.


[EXAMPLE]: Programming 7.088 MHz/LSB into memory channel 12.



### •Programming in memory mode

- ① Select the desired memory channel with [▲]/[▼] in memory mode.
  - Memory channel contents appear in the memory channel readout (below the frequency readout).
  - “--.--.--” appears if the selected memory channel is a blank channel (and does not have contents).
- ② Set the desired frequency and operating mode in memory mode.
  - To program a blank channel, use direct frequency entry with the keypad or memo pads, etc.
- ③ Push [MW] for 2 sec. to program the displayed frequency and operating mode into the memory channel.

[EXAMPLE]: Programming 21.280 MHz/USB into memory channel 18.



## ■ Frequency transferring

The frequency and operating mode in a memory channel can be transferred to the VFO.

Frequency transferring can be performed in either VFO mode or memory mode.


### •Transferring in VFO mode

This is useful for transferring programmed contents to VFO.

- ① Select VFO mode with [VFO/MEMO].
- ② Select the memory channel to be transferred with [▲]/[▼].
  - Memory channel screen is convenient for selecting the desired channel.
  - Memory channel contents appear in the memory channel readout (below the frequency readout).
  - “---.---.---” appears if the selected memory channel is a blank channel. In this case transferring is impossible.
- ③ Push [VFO/MEMO] for 2 sec. to transfer the frequency and operating mode.
  - Transferred frequency and operating mode appear on the frequency readout.

### TRANSFERRING EXAMPLE IN VFO MODE

Operating frequency : 21.320 MHz/USB (VFO)  
 Contents of M-ch 16 : 14.018 MHz/CW



### •Transferring in memory mode


This is useful for transferring frequency and operating mode while operating in memory mode.

- When you have changed the frequency or operating mode in the selected memory channel:
- Displayed** frequency and mode are transferred.
  - Programmed** frequency and mode in the memory channel are not transferred, and they remain in the memory channel.

- ① Select the memory channel to be transferred with [▲]/[▼] in memory mode.
  - And, set the frequency or operating mode if required.
- ② Push [VFO/MEMO] for 2 sec. to transfer the frequency and operating mode.
  - Displayed frequency and operating mode are transferred to the VFO.
- ③ To return to VFO mode, push [VFO/MEMO] momentarily.

### TRANSFERRING EXAMPLE IN MEMORY MODE

Operating frequency : 14.020 MHz/CW (M-ch 16)  
 Contents of M-ch 16 : 14.018 MHz/CW




## Memory names

All memory channels (including scan edges) can be tagged with alphanumeric names of up to 10 characters each.

Capital letters, small letters, numerals, some symbols (! # \$ % & ¥ ? " ' ` ^ + - \* / · : ; = < > ( ) [ ] { } | \_ ~) and spaces can be used.


### Editing (programming) memory names

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-3)MEMORY] to select the memory channel screen.



- ③ Select the desired memory channel.

- ④ Push [(F-4)NAME] to edit memory channel name.
  - A cursor appears and blinks.
  - Memory channel names of blank channels cannot be edited.




- ⑤ Input the desired character by rotating the tuning dial or by pushing the band key for number input.
  - Push [ABC] or [abc] to toggle capital and small letters.
  - Push [123] or [etc] to toggle numerals and symbols.
  - Push [(F-1)◀] or [(F-2)▶] for cursor movement.
  - Push [(F-3)DEL] to delete the selected character.
  - Push [(F-4)SPACE] to input a space.
- ⑥ Push [EXIT] to input and set the name.
  - The cursor disappears.
- ⑦ Repeat steps ③ to ⑥ to program another memory channel's name, if desired.
- ⑧ Push [EXIT] to exit the memory channel screen.

## Memory clearing

Any unnecessary memory channels can be cleared. The cleared memory channels become blank channels.

- ① Select memory mode with [VFO/MEMO].
- ② Select the desired memory channel with [▲]/[▼].
- ③ Push [M-CL] for 2 sec. to clear the contents.
  - The programmed frequency and operating mode disappear.
- ④ To clear other memory channels, repeat steps ② and ③.





## ■ Memo pads

The transceiver has a memo pad function to store frequency and operating mode for easy write and recall. The memo pads are separate from memory channels.

The default number of memo pads is 5, however, this can be increased to 10 in set mode if desired. (p. 71)

Memo pads are convenient when you want to memorize a frequency and operating mode temporarily, such as when you find a DX station in a pile-up, or when a desired station is busy for a long time and you want to temporarily search for other stations.

Use the transceiver's memo pads instead of relying on hastily scribbled notes that are easily misplaced.


### • Writing frequencies and operating modes into memo pads

You can simply write the accessed readout frequency and operating mode by pushing [MP-W].

When you write a 6th frequency and operating mode, the oldest written frequency and operating mode are automatically erased to make room for the new settings.

Each memo pad must have its own unique combination of frequency and operating mode; memo pads having identical settings cannot be written.

Displayed frequency and mode



### • Calling up a frequency from a memo pad


You can simply call up the desired frequency and operating mode of a memo pad by pushing [MP-R] one or more times.

- Both VFO and memory modes can be used.
- The frequency and operating mode are called up, starting from the most recently written.

When you call up a frequency and an operating mode from memo pads with [MP-R], the previously displayed frequency and operating mode are automatically stored in a temporary pad. The frequency and operating mode in the temporary pad can be recalled by pushing [MP-R] one or more times.

- You may think there are 6 memo pads because 6 different frequencies (5 are in memo pads and 1 is in the temporary pad) are called up by [MP-R].

If you change the frequency or operating mode called up from a memo pad with the tuning dial, etc., the frequency and operating mode in the temporary pad are erased.




## Scan types

- The scan function can be used on the main readout only.
- You can operate a scan while operating on a frequency using the dualwatch or split functions. See p. 31 for details.

### PROGRAMMED SCAN


Repeatedly scans between two scan edge frequencies (scan edge memory channels P1 and P2).



This scan operates in VFO mode.

### $\Delta F$ SCAN


Repeatedly scans within  $\Delta F$  span area.



This scan operates in both VFO and memory modes.

### MEMORY SCAN


Repeatedly scans all programmed memory channels.



This scan operates in memory mode.

### SELECT MEMORY SCAN

Repeatedly scans all select memory channels.



This scan operates in memory mode.

## Preparation

### Channels

*For programmed scan:*

Program scan edge frequencies into scan edge memory channels P1 and P2.

*For  $\Delta F$  scan:*

Set the  $\Delta F$  span ( $\Delta F$  scan range) in the scan screen.

*For memory scan:*

Program 2 or more memory channels except scan edge memory channels.

*For select memory scan:*

Designate 2 or more memory channels as select memory channels. To designate the channel as a select memory channel, choose a memory channel, then push [(F-3)SELECT] in the scan screen (memory mode) or in the memory channel screen.

### Scan resume ON/OFF

You can select the scan to resume or cancel when detecting a signal, in set mode. Scan resume ON/OFF must be set before operating a scan. See p. 60 for ON/OFF setting and scan resume condition details.

### Scan speed


Scan speed can be selected from 2 levels, high or low, in set mode. See p. 60 for details.

### Squelch condition

SCAN STARTS WITH	PROGRAMMED SCAN	MEMORY SCAN
<b>SQUELCH OPEN</b>	The scan continues until it is stopped manually, and does not pause even if it detects signals.	Scan pauses on each channel when the scan resume is ON; not applicable when OFF.
<b>SQUELCH CLOSED</b>	Scan stops when detecting a signal. If you set scan resume ON in set mode, the scan pauses for 10 sec. when detecting a signal, then resumes. When a signal disappears while scan is paused, scan resumes 2 sec. later.	


## ■ Programmed scan operation

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select VFO mode.
- ③ Select the desired operating mode.
  - The operating mode can also be changed while scanning.
- ④ Push [(F-4)SCAN] to select the scan screen.



- ⑤ Set [RF/SQL] open or closed.
  - See previous page for scan condition.
  - If the [RF/SQL] control function is set as "AUTO," the squelch is always open in SSB, CW and RTTY modes. See pgs. 3, 68 for details.

- ⑥ Push [(F-1)PROG] to start the programmed scan.
  - Decimal points blink while scanning.




- ⑦ When the scan detects a signal, the scan stops, pauses or ignores it depending on the resume setting and the squelch condition.
- ⑧ To cancel the scan, push [(F-1)PROG].

▨ If the same frequencies are programmed into the scan edge memory channel P1 and P2, programmed scan does not start.


## ■ ΔF scan operation

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select VFO mode or a memory channel.
- ③ Select the desired operating mode.
  - The operating mode can also be changed while scanning.
- ④ Push [(F-4)SCAN] to select the scan screen.



- ⑤ Set [RF/SQL] open or closed.
  - See previous page for scan condition.
  - If the [RF/SQL] control function is set as "AUTO," the squelch is always open in SSB, CW and RTTY modes. See pgs. 3, 68 for details.

- ⑥ Set the ΔF span by pushing [(F-4)ΔF SPAN].
  - ±5 kHz, ±10 kHz, ±20 kHz, ±50 kHz, ±100 kHz, ±500 kHz and ±1000 kHz are selectable.
- ⑦ Set center frequency of the ΔF span.
- ⑧ Push [(F-2)ΔF] to start the ΔF scan.
  - Decimal points blink while scanning.




- ⑨ When the scan detects a signal, the scan stops, pauses or ignores it depending on the resume setting and the squelch condition.
- ⑩ To cancel the scan, push [(F-2)ΔF].


## ■ Fine programmed scan/fine $\Delta F$ scan

Fine scan functions as programmed or  $\Delta F$  scan, but scan speed decreases when the squelch opens but does not stop. The scanning tuning step shifts from 50 Hz to 10 Hz while the squelch opens.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-4)SCAN] to select the scan screen.
- ③ Set for programmed scan or  $\Delta F$  scan as described on previous page.
- ④ Push [(F-1)PROG] or [(F-2) $\Delta F$ ] to start a scan.
  - Decimal points blink while scanning.




- ⑤ Push [(F-3)FINE] to start a fine scan.
  - "FINE PROGRAM SCAN" or "FINE  $\Delta F$  SCAN" appears.




- ⑥ When the scan detects a signal, the scan speed decreases but does not stop.
- ⑦ Push [(F-1)PROG] or [(F-2) $\Delta F$ ] to stop the scan; push [(F-3)FINE] to cancel the fine scan.

## ■ Memory scan operation

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select memory mode.
- ③ Select the desired operating mode.
  - The operating mode can also be changed while scanning.
- ④ Push [(F-4)SCAN] to select the scan screen.



- ⑥ Push [(F-1)MEMO] to start the memory scan.
  - Decimal points blink while scanning.




- ⑤ Set [RF/SQL] open or closed.
  - See p. 56 for scan condition.
  - If the [RF/SQL] control function is set as "AUTO," the squelch is always open in SSB, CW and RTTY modes. See pgs. 3, 68 for details.

- ⑦ When the scan detects a signal, the scan stops, pauses or ignores it depending on the resume setting and the squelch condition.
- ⑧ To cancel the scan, push [(F-1)MEMO].

/// 2 or more memory channels must be programmed for memory scan to start.


## ■ Select memory scan operation

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select memory mode.
- ③ Select the desired operating mode.
  - The operating mode can also be changed while scanning.
- ④ Push [(F-4)SCAN] to select the scan screen.



- ⑤ Set [RF/SQL] open or closed.
  - See p. 56 for scan condition.
  - If the [RF/SQL] control function is set as "AUTO," the squelch is always open in SSB, CW and RTTY modes. See pgs. 3, 68 for details.

- ⑥ Push [(F-1)MEMO] to start the memory scan.
  - Decimal points blink while scanning.
- ⑦ Push [(F-3)SELECT] to start select memory scan; push [(F-3)SELECT] again to return to memory scan, if desired.




- ⑧ When the scan detects a signal, the scan stops, pauses or ignores it depending on the resume setting and the squelch condition.
- ⑨ To cancel the scan, push [(F-1)MEMO].

2 or more memory channels must be designated as select memory channels for select memory scan to start.

## ■ Setting select memory channels


- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Select memory mode.
- ③ Push [(F-4)SCAN] to select the scan screen.



- ④ Select the desired memory channel to set as select memory channel.

- ⑤ Push [(F-3)SELECT] to set the memory channel as a select memory or not.

"★" appears for select memory channels.



- ⑥ Repeat steps ④ to ⑤ to program another memory channel as a select memory channel, if desired.
- ⑦ Push [EXIT] to exit the scan screen.

Select memory channels can also be set in the memory channel screen. (p. 51)


## ■ Scan set mode

Scan set mode is used for programming scanning speed and scan resume condition.


### •Scan speed

The transceiver has 2 speeds for scanning, high and low.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-4)SCAN] to select the scan screen.



- ③ Push [(F-5)SET] to select the scan set mode screen.
- ④ Push [(F-1)▲] to select the scan speed item.




- ⑤ Rotate the tuning dial to select the scan speed.
  - Push [(F-3)DEF] to select the default condition.
- ⑥ Push [EXIT] twice to exit the set mode.

### •Scan resume condition

This item sets the scan resume function ON or OFF. ON: scan resumes 10 sec. after stopping on a signal (or 2 sec. after a signal disappears); OFF: scan does not resume after stopping on a signal.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-4)SCAN] to select the scan screen.
- ③ Push [(F-5)SET] to select the scan set mode screen.
- ④ Push [(F-2)▼] to select the scan resume condition item.




- ⑤ Rotate the tuning dial to turn the scan resume function ON or OFF.
  - Push [(F-3)DEF] to select the default condition.
- ⑥ Push [EXIT] twice to exit the set mode.

## ■ Tone scan


The transceiver can detect the subaudible tone frequency in a received signal. By monitoring a signal that is being transmitted on a repeater input frequency, you can determine the tone frequency required to access the repeater.

- ① Set the desired frequency or memory channel to be checked for a tone frequency.
- ② Push [AM/FM] one or more times to select FM mode.
- ③ Push [(F-5)TONE] for 2 sec. to enter the tone frequency screen.



- ④ Push [(F-1)▲] or [(F-2)▼] to check the repeater tone frequency or tone squelch frequency, respectively. (pgs. 46, 47)

- ⑤ Push [(F-5)T-SCAN] to start the tone scan.
  - “SCAN” flashes while scanning.




- ⑥ When the tone frequency is detected, the tone scan pauses.
  - The tone frequency is set temporarily on a memory channel. Program into the memory channel to store the tone frequency permanently.
  - The decoded tone frequency is used for the repeater tone frequency or tone squelch frequency.
- ⑦ To stop the scan, push [EXIT].
- ⑧ Push [EXIT] to exit the tone frequency screen.


## Setting the current time

The transceiver has a built-in 24-hour clock with power-off and power-on timer functions. This is useful when logging QSO's and so on. The clock indication is always displayed except after pushing [F-INP].

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-5)SET] then [(F-3)TIME] to enter timer set mode.
- ③ Push [(F-1)▲] or [(F-2)▼] to select the time adjustment item.




- ④ Set the current time using the tuning dial.
  - “TIME-set push [SET]” blinks.



- ⑤ Push [(F-4)SET] to enter the set time.
  - Push [EXIT] to cancel the setting.

Set time appears.



- ⑥ Push [EXIT] twice to exit timer set mode.


## Setting power-on time

The transceiver can be set to turn ON automatically at a specified time.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-5)SET] then [(F-3)TIME] to enter timer set mode.
- ③ Push [(F-1)▲] or [(F-2)▼] to select the power-on time item.



- ④ Set the desired power-on time using the tuning dial.
  - “TIMER-set push [SET]” blinks.




- ⑤ Push [(F-4)SET] to enter the set time.
  - Push [EXIT] to cancel the setting.
- ⑥ Push [EXIT] twice to exit timer set mode.




## ■ Setting power-off period

The transceiver can be set to turn OFF automatically after being activated via the power-on timer. The power-off period can be set to 5–120 min. in 5 min. steps.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-5)SET] then [(F-3)TIME] to enter timer set mode.
- ③ Push [(F-1)▲] or [(F-2)▼] to select the power-off time item.




- ④ Set the desired power-off time using the tuning dial.
  - “TIMER – set push [SET]” blinks.



- ⑤ Push [(F-4)SET] to enter the set time.
  - Push [EXIT] to cancel the setting.
- ⑥ Push [EXIT] twice to exit timer set mode.

## ■ Timer operation

- ① Preset the power-on time and power-off period as described previously.
- ② Push [POWER] momentarily to turn the timer function ON.
  - The [POWER] light lights when the timer function is ON.



- ③ Push [POWER] for 2 sec. to turn the power OFF.
  - The [POWER] light lights continuously.

- ④ When the set time arrives, the power is automatically turned ON.
- ⑤ The transceiver emits 10 beeps and turns OFF after the power-off period elapses.
  - The [POWER] light blinks while beeping.
  - Push [POWER] momentarily to cancel the power-off timer, if desired.


## ■ Set mode description

Set mode is used for programming infrequently changed values or conditions of functions. This transceiver has a level set mode, display set mode, timer set mode and miscellaneous (others) set mode.



### •Set mode operation

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-5)SET] to select the set mode screen.
- ③ Push [(F-1)LEVEL], [(F-2)DISP], [(F-3)TIME] or [(F-4)OTHERS] to enter the desired set mode.
- ④ For display or miscellaneous (others) set mode, push [(F-5)WIDE] to toggle wide and normal screen.
- ⑤ Push [(F-1)▲] or [(F-2)▼] to select the desired item.



- ⑥ Set the desired condition using the tuning dial.
  - Push [(F-3)DEF] to select a default condition or value.
- ⑦ For timer set mode, push [(F-4)SET] to enter the set time.
- ⑧ Push [EXIT] twice to exit the set mode.



### •Start up screen




### •Set mode screen



### •Level set mode (p. 65)



### •Display set mode (p. 66)



### •Timer set mode (pgs. 62, 67)



### •Miscellaneous (others) set mode (p. 68)



## ■ Level set mode

### SSB Tx Tone (Bass)

This item adjusts the bass level of the transmit audio tone in SSB mode from -5 dB to +5 dB in 1 dB steps.

 0dB

0 dB (default)

### SSB Tx Tone (Treble)

This item adjusts the treble level of the transmit audio tone in SSB mode from -5 dB to +5 dB in 1 dB steps.

 0dB

0 dB (default)

### Monitor Level

This item adjusts the transmit IF signal monitor level from 0 % to 100 % in 1 % steps.

 50%

50 % (default)

See p. 35 for details.

### Side Tone Level

This item adjusts the CW side tone level from 0 % to 100 % in 1 % steps.

 50%

50 % (default)

See p. 35 for details.

### Side Tone Level Limit

This item allows you to set a maximum volume level for CW side tones. CW side tones are linked to the [AF] control until a specified volume level is reached—further rotation of the [AF] control will not increase the volume of the CW side tones.

**ON**

CW side tone level is limited with [AF] (default)

**OFF**

CW side tone level is linked to [AF]

### Beep Level

This item adjusts the volume level for confirmation beep tones from 0 % to 100 % in 1 % steps. When beep tones are turned OFF, this setting has no effect.

 50%

50 % (default)

### Beep Level Limit

This item allows you to set a maximum volume level for confirmation beep tones. Confirmation beep tones are linked to the [AF] control until a specified volume level is reached—further rotation of the [AF] control will not increase the volume of the beep tones.

**ON**

Beep level is limited with [AF] (default)

**OFF**


Beep level is linked to [AF]

## ■ Display set mode

/// To adjust the LCD contrast or backlight, wait until the LCD becomes stable (10 min. or more after turning power ON). This is an inherent characteristic of LCDs and LCD backlights and does not indicate a transceiver malfunction.


### Contrast (LCD)

This item adjusts the contrast of the LCD from 0 % to 100 % in 1 % steps.




### Backlight (LCD)

This item adjusts the brightness of the LCD from 0 % to 100 % in 1 % steps.




### Horizon

This item adjusts the horizontal position of the LCD from 1 to 8.



### Backlight (switches)

This item adjusts the brightness of the switches from 1 to 8.



### Display Type

This item sets the LCD screen type. There are 4 selectable types: A, B, C and D.

**A**  
A-type LCD screen (default)

### Display Font

This item sets the font of the frequency readouts. There are 7 selectable fonts: Basic 1, Basic 2, Pop, 7seg (7 segment numeral), Italic 1, Italic 2 and Classic.

**Basic1**  
Basic 1 font (default)

### Memory Name

This item sets the memory name indication ON and OFF.

See p. 54 for details.

<b>ON</b>	<b>OFF</b>
Memory name is displayed. (default)	Memory name is not displayed.


## ■ Display set mode (continued)

### My Call

Your call sign, etc. can be displayed in the opening screen when turning power ON. Up to 10 characters can be programmed.

Capital letters, numerals, some symbols (– / ·) and spaces can be used.

- ① Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ② Push [(F-5)SET] then [(F-2)DISP] to select the display set mode screen.
- ③ Push [(F-2)▼] one or more times to select the 'My Call' item.



- ④ Push [(F-4)EDIT] to edit.
  - A cursor appears and blinks.



- ⑤ Input the desired character by rotating the tuning dial or by pushing the band key for number input.
  - Push [ABC] to select capital letters.
  - Push [123] or [etc] to toggle numerals and symbols.
  - Push [(F-1)◀] or [(F-2)▶] for cursor movement.
  - Push [(F-3)DEL] to delete the selected character.
  - Push [(F-4)SPACE] to input a space.
- ⑥ Push [EXIT] to input the set name.
  - The cursor disappears.
- ⑦ Push [EXIT] to exit the set mode screen.

### •Opening screen example



## ■ Timer set mode

### Time (now)

This item sets the current time for the built-in 24-hour clock.

See p. 62 for details.

**15:00**

Push [(F-4)SET] to enter the time.

### Power-ON timer set

This item sets the power-on time.

See p. 62 for details.

**15:00**

Push [(F-4)SET] to enter the time.

### Power-OFF Period

This item sets the power-off period for automatic shut-down after the power-on timer has turned power ON.

See p. 63 for details.

**60min**

Push [(F-4)SET] to enter the time.

## ■ Miscellaneous (others) set mode

### Calibration Marker

This item is used for a simple frequency check of the transceiver.

See p. 76 for calibration procedure.

☐ Turn the calibration marker OFF after checking the frequency of the transceiver.

**ON**

Calibration marker ON

**OFF**

Calibration marker OFF (default)

### Beep (Confirmation)

A beep sounds each time a switch is pushed to confirm it. This function can be turned OFF for silent operation.

The volume level can be set in level set mode. (p. 65)

**ON**

Confirmation beep ON (default)

**OFF**

Confirmation beep OFF

### Beep (Band Edge)

A beep sounds when an operating frequency enters or exits an amateur band. This functions independent of the confirmation beep setting (above).

The volume level can be set in level set mode. (p. 65)

**ON**

Band edge beep ON (default)

**OFF**

Band edge beep OFF

### RF/SQL Control

The [RF/SQL] control can be set as the RF/squelch control (default), the squelch control only (RF gain is fixed at maximum) or 'Auto' (RF gain control in SSB, CW and RTTY; squelch control in AM and FM).

See p. 3 for details.

**RF+SQL**

[RF/SQL] control as RF/squelch control (default)

**SQL**

[RF/SQL] control as squelch control

**AUTO**

[RF/SQL] control as RF gain control in SSB, CW and RTTY; squelch control in AM and FM

### Quick Dualwatch

When this item is set to ON, pushing [DUALWATCH] for 2 sec. sets the sub readout frequency to the main readout frequency and activates dualwatch operation.

See p. 31 for details.

**ON**

Quick dualwatch ON (default)

**OFF**

Quick dualwatch OFF

### Quick SPLIT

When this item is set to ON, pushing [SPLIT] for 2 sec. sets the sub readout frequency to the main readout frequency and activates split operation.

See p. 33 for details.

**ON**

Quick split ON (default)

**OFF**

Quick split OFF

## ■ Miscellaneous (others) set mode (continued)

<p><b>FM SPLIT Offset (HF)</b></p> <p>This item sets the offset (difference between transmit and receive frequencies) for the quick split function. However, this setting is used for HF bands in FM mode only and is used to input the repeater offset for an HF band.</p> <p>The offset frequency can be set from -4 MHz to +4 MHz in 1 kHz steps.</p>	<p><b>-0.100MHz</b> Minus 0.1 MHz offset (default)</p>	<p><b>-4.000MHz</b> Minus 4.0 MHz offset</p>
<p><b>FM SPLIT Offset (50M)</b></p> <p>This item sets the offset (difference between transmit and receive frequencies) for the quick split function. However, this setting is used for 50 MHz band FM mode only, and is used to input the repeater offset for the 50 MHz band.</p> <p>The offset frequency can be set from -4 MHz to +4 MHz in 1 kHz steps.</p>	<p><b>-1.000MHz</b> Minus 1.0 MHz offset (default)</p>	<p><b>+4.000MHz</b> Plus 4.0 MHz offset</p>
<p><b>SPLIT Lock</b></p> <p>When this item is ON, the tuning dial can be used to adjust the transmit frequency while pushing [XFC] even while the lock function is activated.</p> <p>See p. 32 for split frequency operation details.</p>	<p><b>ON</b> Split lock function ON</p>	<p><b>OFF</b> Split lock function OFF (default)</p>
<p><b>Tuner (Auto Start)</b></p> <p>The internal antenna tuner has an automatic start capability which starts tuning if the SWR is higher than 1.5-3.</p> <p>When "OFF" is selected, the tuner remains OFF even when the SWR is poor (1.5-3). When "ON" is selected, automatic tune starts even when the tuner is turned OFF.</p>	<p><b>ON</b> Automatic tuner start ON</p>	<p><b>OFF</b> Automatic tuner start OFF (default)</p>
<p><b>Tuner (PTT Start)</b></p> <p>Tuning of the internal antenna tuner can be started automatically at the moment the PTT is pushed after the operating frequency is changed (more than 1% from last-tuned frequency).</p>	<p><b>ON</b> Automatic PTT start ON</p>	<p><b>OFF</b> Automatic PTT start OFF (default)</p>

## ■ Miscellaneous (others) set mode (continued)

### [ANT] Switch

You can set the antenna connector selection to automatic, manual or non-selection (when using 1 antenna only).

When "Auto" is selected, the antenna switch is activated and the band memory memorizes the selected antenna. See p. 45 for details.

When "Manual" is selected, the antenna switch is activated and selects an antenna manually.

When "OFF" is selected, the antenna switch is not activated and does not function. The [ANT1] connector is always selected in this case.

<b>Auto</b>	Antenna switch is activated and the selection is automatically memorized. (default)
<b>Manual</b>	Antenna switch is activated.
<b>OFF</b>	Antenna switch is deactivated and [ANT1] is always selected.

### RTTY Mark Frequency

This item selects the RTTY mark frequency. RTTY mark frequency is toggled between 1275, 1615 and 2125 Hz.

<b>2125</b>	<b>1275</b>
2125 Hz RTTY mark frequency (default)	1275 Hz RTTY mark frequency

### RTTY Shift Width

This item adjusts the RTTY shift width. There are 3 selectable values: 170, 200 and 425 Hz.

<b>170</b>	<b>425</b>
170 Hz RTTY shift frequency (default)	425 Hz RTTY shift frequency

### RTTY Keying Polarity

This item selects the RTTY keying polarity. Normal or reverse keying polarity can be selected.

When reverse polarity is selected, Mark and Space are reversed.

- Normal : Key open/close = Mark/Space
- Reverse : Key open/close = Space/Mark

<b>NORMAL</b>	<b>REVERSE</b>
Normal polarity (default)	Reverse polarity

### RTTY Decode USOS

This item selects the USOS (UnShift On Space) function of the internal RTTY decoder.

See p. 41 for details.

<b>ON</b>	<b>OFF</b>
Decode as letter code (default)	Decode as character code



## ■ Miscellaneous (others) set mode (continued)

<p><b>RTTY Decode New Line Code</b></p> <p>This item selects the new line code of the internal RTTY decoder. See p. 41 for details.</p> <p>CR : Carriage Return LF : Line Feed</p>	<p><b>CR,LF,CR+LF</b></p> <p>CR, LF and CR+LF (default)</p>	<p><b>CR+LF</b></p> <p>CR+LF only</p>
<p><b>Speech Language</b></p> <p>When the optional UT-102 VOICE SYNTHESIZER UNIT is installed, you can select between English and Japanese as the language.</p> <p>See p. 73 for unit installation.</p>	<p><b>English</b></p> <p>English announcement (default)</p>	<p><b>Japanese</b></p> <p>Japanese announcement</p>
<p><b>Speech Speed</b></p> <p>When the optional UT-102 VOICE SYNTHESIZER UNIT is installed, you can select between faster or slower synthesizer output.</p> <p>See p. 73 for unit installation.</p>	<p><b>HIGH</b></p> <p>Faster announcement (default)</p>	<p><b>LOW</b></p> <p>Slower announcement</p>
<p><b>Speech S-Level</b></p> <p>When the optional UT-102 VOICE SYNTHESIZER UNIT is installed, you can have frequency, mode and signal level announcement. Signal level announcement can be deactivated if desired.</p> <p>When "OFF" is selected, the signal level is not announced.</p> <p>See p. 73 for unit installation.</p>	<p><b>ON</b></p> <p>Signal level announcement (default)</p>	<p><b>OFF</b></p> <p>No signal level announcement</p>
<p><b>Memo Pad Numbers</b></p> <p>This item sets the number of memo pad channels available. 5 or 10 memo pads can be set.</p>	<p><b>5</b></p> <p>5 memo pads (default)</p>	<p><b>10</b></p> <p>10 memo pads</p>
<p><b>MAIN DIAL Auto TS</b></p> <p>This item sets the auto tuning step function. When rotating the tuning dial rapidly, the tuning step automatically changes several times as selected.</p> <p>There are 2 type of auto tuning steps: HIGH (Fastest) and LOW (Faster).</p>	<p><b>HIGH</b></p> <p><b>LOW</b></p> <p><b>OFF</b></p>	<p>Auto tuning step is turned ON. Fastest tuning step during rapid rotation (default)</p> <p>Auto tuning step is turned ON. Faster tuning step during rapid rotation</p> <p>Auto tuning step is turned OFF.</p>

## ■ Miscellaneous (others) set mode (continued)

### Mic UP/Down Speed

This item sets the rate at which frequencies are scanned when the microphone [UP]/[DN] switches are pushed and held. High or low can be selected.

#### HIGH

High speed (default,  
50 tuning steps/sec.)

#### LOW

Low speed  
(25 tuning steps/sec.)

### CI-V baud rate

This item sets the data transfer rate. 300, 1200, 4800, 9600, 19200 bps and "AUTO" are available.

When "AUTO" is selected, the baud rate is automatically set according to the connected controller or remote controller.

#### AUTO

Auto baud rate  
(default)

#### 19200

19200 bps

### CI-V address

To distinguish equipment, each CI-V transceiver has its own Icom standard address in hexadecimal code. The IC-756PRO's address is 5Ch.

When 2 or more IC-756PRO's are connected to an optional CT-17 CI-V LEVEL CONVERTER, rotate the tuning dial to select a different address for each IC-756PRO in the range 01h to 7Fh.

#### 5Ch

Address of 5Ch  
(default)

#### 7Fh

Address of 7Fh

### CI-V transceive

Transceive operation is possible with the IC-756PRO connected to other Icom HF transceivers or receivers.

When "ON" is selected, changing the frequency, operating mode, etc. on the IC-756PRO automatically changes those of connected transceivers (or receivers) and vice versa.

#### ON

Transceive ON  
(default)

#### OFF

Transceive OFF

### CI-V with IC-731

When connecting the IC-756PRO to the IC-735 for transceive operation, you must change the operating frequency data length to 4 bytes.

• This item must be set to "ON" only when operating transceiver with the IC-735.

#### ON

4 bytes of frequency data

#### OFF


5 bytes of frequency data  
(default)

## ■ Opening the transceiver's case


Follow the case and cover opening procedures shown here when you want to install an optional unit or adjust the internal units, etc.

**CAUTION:** DISCONNECT the DC power cable from the transceiver before performing any work on the transceiver. Otherwise, there is danger of electric shock and/or equipment damage.

- ① Remove 2 screws from the left side of the transceiver to remove the carrying handle as shown below.



- ② Remove 7 screws from the top of the transceiver and 4 screws from the sides, then lift up the top cover.
- ③ Turn the transceiver upside down.
- ④ Remove 6 screws from the bottom of the transceiver, then lift up the bottom cover.




## ■ UT-102 VOICE SYNTHESIZER UNIT

The UT-102 announces the accessed readout's frequency, mode, etc. (S-meter level can also be announced—p. 71) in a clear, electronically-generated voice, in English (or Japanese).

➡ Push [SPEECH] to announce the frequency, etc.

- ① Remove the top and bottom covers as shown above.
- ② Remove the protective paper attached to the bottom of the UT-102 to expose the adhesive strip.
- ③ Plug UT-102 into J3502 on the MAIN unit as shown in the diagram at right.
- ④ Return the top and bottom covers to their original positions.



# 11 MAINTENANCE

## ■ Troubleshooting

The following chart is designed to help you correct problems which are not equipment malfunctions.

If you are unable to locate the cause of a problem or solve it through the use of this chart, contact your nearest Icom Dealer or Service Center.

	PROBLEM	POSSIBLE CAUSE	SOLUTION	REF.
POWER	Power does not come on when the [POWER] switch is pushed.	<ul style="list-style-type: none"> <li>•DC power cable is improperly connected.</li> <li>•Fuse is blown.</li> </ul>	<ul style="list-style-type: none"> <li>•Reconnect the DC power cable correctly.</li> <li>•Check for the cause, then replace the fuse with a spare one. (Fuses are installed in the DC power cable and the internal PA unit.)</li> </ul>	p. 17 p. 75
	RECEIVE	No sound comes from the speaker.	<ul style="list-style-type: none"> <li>•Volume level is too low.</li> <li>•The squelch is closed.</li> <li>•The transceiver is in the transmitting condition.</li> </ul>	<ul style="list-style-type: none"> <li>•Rotate [AF] clockwise to obtain a suitable listening level.</li> <li>•Rotate [RF/SQL] to 10 o'clock position to open the squelch.</li> <li>•Push [TRANSMIT] to receive or check the SEND line of an external unit, if desired.</li> </ul>
Sensitivity is low.		<ul style="list-style-type: none"> <li>•The antenna is not connected properly.</li> <li>•The antenna for another band is selected.</li> <li>•The antenna is not properly tuned.</li> <li>•The attenuator is activated.</li> </ul>	<ul style="list-style-type: none"> <li>•Reconnect to the antenna connector.</li> <li>•Select an antenna suitable for the operating frequency.</li> <li>•Push [TUNER] for 2 sec. to manually tune the antenna.</li> <li>•Push [ATT] one or more times to select "ATT OFF."</li> </ul>	— pgs. 5, 45 p. 48 p. 5
Receive audio is distorted.		<ul style="list-style-type: none"> <li>•The operating mode is not selected correctly.</li> <li>•PBT function is activated.</li> <li>•Noise blanker function is activated.</li> <li>•Preamp is activated.</li> <li>•The noise reduction is activated and the [NR] control is set too far clockwise.</li> </ul>	<ul style="list-style-type: none"> <li>•Select a suitable operating mode.</li> <li>•Push [PBT CLR] for 2 sec. to reset the function.</li> <li>•Push [NB] to turn the function OFF.</li> <li>•Push [P.AMP] once or twice to turn the function OFF.</li> <li>•Set the [NR] control for maximum readability.</li> </ul>	p. 26 p. 26 p. 27 p. 5 p. 27
The [ANT] switch does not function.		<ul style="list-style-type: none"> <li>•The antenna switch has not been activated.</li> </ul>	<ul style="list-style-type: none"> <li>•Set the antenna switch in set mode to "Auto" or "Manual."</li> </ul>	p. 45
TRANSMIT	Transmitting is impossible.	<ul style="list-style-type: none"> <li>•The operating frequency is not set to a ham band.</li> </ul>	<ul style="list-style-type: none"> <li>•Set the frequency to a ham band.</li> </ul>	p. 24
	Output power is too low.	<ul style="list-style-type: none"> <li>•[RF POWER] is set too far counterclockwise.</li> <li>•[MIC GAIN] is set too far counterclockwise.</li> <li>•The antenna for another band is selected.</li> <li>•The antenna is not properly tuned.</li> </ul>	<ul style="list-style-type: none"> <li>•Rotate [RF POWER] clockwise.</li> <li>•Set [MIC GAIN] to a suitable position.</li> <li>•Select an antenna suitable for the operating frequency.</li> <li>•Push [TUNER] for 2 sec. to manually tune the antenna.</li> </ul>	p. 3 p. 2 p. 5 p. 48
	No contact possible with another station.	<ul style="list-style-type: none"> <li>•RIT or ΔTX function is activated.</li> <li>•Split frequency function and/or dualwatch are activated.</li> </ul>	<ul style="list-style-type: none"> <li>•Push [RIT] or [ΔTX] to turn the function OFF.</li> <li>•Push [SPLIT] and/or [DUALWATCH] to turn the function OFF.</li> </ul>	p. 6 pgs. 7, 31, 32
	Transmitted signals are distorted.	<ul style="list-style-type: none"> <li>•[MIC GAIN] is set too far clockwise.</li> </ul>	<ul style="list-style-type: none"> <li>•Set [MIC GAIN] to a suitable position.</li> </ul>	p. 2
	Repeater cannot be accessed.	<ul style="list-style-type: none"> <li>•Split frequency function is not activated.</li> <li>•Programmed subaudible tone frequency is wrong.</li> </ul>	<ul style="list-style-type: none"> <li>•Push [SPLIT] to turn the function ON.</li> <li>•Reset the frequency using set mode.</li> </ul>	p. 7 p. 46
SCAN	Programmed scan does not stop.	<ul style="list-style-type: none"> <li>•Squelch is open.</li> <li>•[RF/SQL] is assigned to RF gain control and squelch is open.</li> </ul>	<ul style="list-style-type: none"> <li>•Set [RF/SQL] to the threshold point.</li> <li>•Reset [RF/SQL] control assignment and set it to the threshold point.</li> </ul>	p. 3 pgs. 3, 68
	Programmed scan does not start.	<ul style="list-style-type: none"> <li>•The same frequencies have been programmed in scan edge memory channels P1 and P2.</li> </ul>	<ul style="list-style-type: none"> <li>•Program different frequencies in scan edge memory channels P1 and P2.</li> </ul>	p. 52
	Memory scan does not start.	<ul style="list-style-type: none"> <li>•2 or more memory channels have not been programmed.</li> </ul>	<ul style="list-style-type: none"> <li>•Program 2 or more memory channels.</li> </ul>	p. 52
	Select memory scan does not start.	<ul style="list-style-type: none"> <li>•2 or more memory channels have not been designated as select channels.</li> </ul>	<ul style="list-style-type: none"> <li>•Designate 2 or more memory channels as select channels for the scan.</li> </ul>	pgs. 51, 59

	PROBLEM	POSSIBLE CAUSE	SOLUTION	REF.
DISPLAY	The displayed frequency does not change properly.	<ul style="list-style-type: none"> <li>•The dial lock function is activated.</li> <li>•A set mode screen is selected.</li> <li>•The internal CPU has malfunctioned.</li> </ul>	<ul style="list-style-type: none"> <li>•Push [LOCK] to deactivate the function.</li> <li>•Push [EXIT] one or more times to exit the set mode screen.</li> <li>•Reset the CPU.</li> </ul>	p. 6 pgs. 11, 64 p. 22


## ■ Fuse replacement

If a fuse blows or the transceiver stops functioning, try to find the source of the problem, and replace the damaged fuse with a new, rated fuse.

**CAUTION:** DISCONNECT the DC power cable from the transceiver when changing a fuse.

The IC-756PRO has 2 types of fuses installed for transceiver protection.


- DC power cable fuses ..... FGB 30 A
- Circuitry fuse ..... FGB 5 A




### CIRCUITRY FUSE REPLACEMENT

The 13.8 V DC from the DC power cable is applied to all units in the IC-756PRO, except for the power amplifier, through the circuitry fuse. This fuse is installed in the PA unit.

- ① Remove the top cover as shown on p. 73.
- ② Remove 11 screws from the PA shielding plate, then remove the plate.



- ③ Replace the circuitry fuse as shown in the diagram below.
- ④ Replace the PA shielding plate and top cover.




## ■ Clock backup battery replacement

The transceiver has a lithium backup battery (CR2032) inside for clock and timer functions. The usual life of the backup battery is approximately 2 years.

When the backup battery is exhausted, the transceiver transmits and receives normally but cannot retain the current time.

See p. 77 for battery location.




## ■ Tuning dial brake adjustment

The tension of the tuning dial may be adjusted to suit your preference.

The brake adjustment screw is located on the right side of the tuning dial. See the figure at right.

Turn the brake adjustment screw clockwise or counterclockwise to obtain a comfortable tension level while turning the dial continuously and evenly in one direction.




## ■ Frequency calibration (approximate)

A very accurate frequency counter is required to calibrate the frequency of the transceiver. However, a rough check may be performed by receiving radio station WWV, or other standard frequency signals.

**CAUTION:** Your transceiver has been thoroughly adjusted and checked at the factory before being shipped. You should not calibrate frequencies, except for special reasons.

- ① Push [SSB] to select USB mode.
- ② Push [PBT CLR] for 2 sec. to clear the PBT settings and make sure that the RIT/ΔTX function is not activated.
- ③ Set the frequency to the standard frequency station minus 1 kHz.
  - When receiving WWV (10.000.00 MHz) as a standard frequency, set the operating frequency for 9.999.00 MHz.
  - Other standard frequencies can also be used.




- ④ Push [EXIT] one or more times to close a multi-function screen, if necessary.
- ⑤ Push [(F-5)SET] to select the set mode screen.
- ⑥ Push [(F-4)OTHERS] to enter miscellaneous (others) set mode.

- ⑦ Push [(F-1)▲] several times to select the “Calibration marker” item.
- ⑧ Rotate the tuning dial clockwise to turn the calibration marker ON.
  - Side tone may be heard.




- ⑨ Adjust the calibration pot on the right side panel of the transceiver for a zero beat with the received standard signal as shown below.
  - Zero beat means that two signals are exactly the same frequency, resulting in a single tone being emitted.




- ⑩ Rotate the tuning dial counterclockwise to turn the calibration marker OFF.
- ⑪ Push [EXIT] twice to exit set mode.

## •Top view



## •Bottom view



# 13 CONTROL COMMAND

## ■ Remote jack (CI-V) information


### •CI-V connection example

The transceiver can be connected through an optional CT-17 CI-V LEVEL CONVERTER to a personal computer equipped with an RS-232C port. The Icom Communications Interface-V (CI-V) controls the following functions of the transceiver.


Up to 4 Icom CI-V transceivers or transceivers can be connected to a personal computer equipped with an RS-232C port. See p. 72 for setting the CI-V condition using set mode.

### •Data format


The CI-V system can be operated using the following data formats. Data formats differ according to command numbers. A data area or sub command is added for some commands.




### CONTROLLER TO IC-756PRO




### OK MESSAGE TO CONTROLLER



### IC-756PRO TO CONTROLLER



### NG MESSAGE TO CONTROLLER





## •Command table

Command	Sub command	Description
00	—	Send frequency data
01	Same as command 06	Send mode data
02	—	Read band edge frequencies
03	—	Read operating frequency
04	—	Read operating mode
05	—	Set frequency data
06	00	Set LSB
	01	Set USB
	02	Set AM
	03	Set CW
	04	Set RTTY
	05	Set FM
	07	Set CW-R
	08	Set RTTY-R
	07	—
B0		Exchange main and sub readouts
B1		Equalize main and sub readouts
C0		Turn the dualwatch OFF
C1		Turn the dualwatch ON
D0		Select main readout
08	—	Select memory mode
	0001 – 0101*1	Select memory channel *1P1=0100, P2=0101
09	—	Memory write
0A	—	Memory to VFO
0B	—	Memory clear
0E	00	Scan stop
	01	Programmed/memory scan start
	02	Programmed scan start
	03	$\Delta$ F scan start
	12	Fine programmed scan start
	13	Fine $\Delta$ F scan start
	22	Memory scan start
	23	Select memory scan start
	A1 – A7	Set $\Delta$ F scan span (5 kHz, A2=±10 kHz, A3=±20 kHz, A4=±50 kHz, A5=±100 kHz, A6=±500 kHz, A7=±1 MHz)
	B0	Set as non-select channel
	B1	Set as select channel
D0	Set scan resume OFF	
D3	Set scan resume ON	
0F	00	Turn the split function OFF
	01	Turn the split function ON
10	00	10 Hz (1 Hz) tuning step
	01	100 Hz tuning step
	02	1 kHz tuning step
	03	5 kHz tuning step
	04	9 kHz tuning step
	05	10 kHz tuning step
	06	12.5 kHz tuning step
	07	20 kHz tuning step
	08	25 kHz tuning step
11	00	Attenuator OFF
	06	Attenuator ON (6 dB)
	12	Attenuator ON (12 dB)
	18	Attenuator ON (18 dB)
12	00	Select [ANT1]
	01	Select [ANT2] (Add 0 or 1 to turn [RX ANT] OFF or ON, respectively.)
13	00	Announce with voice synthesizer
	01	(00=all data; 01=frequency and S-meter level; 02=receive mode)
	02	

Command	Sub command	Description
14	01 + level data	[AF] level setting (0=max. CCW to 255=max. CW)
	02 + level data	[RF] level setting (0=max. CCW to 255=11 o'clock)
	03 + level data	[SQL] level setting (0=11 o'clock to 255=max. CW)
	06 + level data	[NR] level setting (0=min. to 255=max.)
	07 + level data	Inside [TWIN PBT] setting or IF shift setting (0=max. CCW, 128=center, 255=max. CW)
	08 + level data	Outside [TWIN PBT] setting (0=max. CCW, 128=center, 255=max. CW)
	09 + level data	[CW PITCH] setting (0=low pitch to 255=high pitch)
	0A + level data	[RF POWER] setting (0=min. to 255=max.)
	0B + level data	[MIC GAIN] setting (0=min. to 255=max.)
	0C + level data	[KEY SPEED] setting (0=slow to 255=fast)
	0D + level data	[NOTCH] setting (0=low freq. to 255=high freq.)
	0E + level data	[COMP] setting (0=min. to 255=max.)
0F + level data	[BK-IN DELAY] setting (0=short delay to 255=long delay)	
10 + level data	[BAL] setting (0=max. CCW, 128=center, 255=max. CW)	
15	01	Read squelch condition
	02	Read S-meter level
16	02	Set preamp (0=OFF; 1=preamp 1; 2=preamp 2)
	12	Set AGC time constant (1=FAST; 2=MID; 3=SLOW)
	22	Set noise blanker (0=OFF; 1=ON)
	40	Set noise reduction (0=OFF; 1=ON)
	41	Set auto notch (0=OFF; 1=ON)
	42	Set repeater tone (0=OFF; 1=ON)
	43	Set tone squelch (0=OFF; 1=ON)
	44	Set speech compressor (0=OFF; 1=ON)
	45	Set monitor (0=OFF; 1=ON)
	46	Set VOX function (0=OFF; 1=ON)
47	Set break-in (0=OFF; 1=ON)	
48	Set manual notch (0=OFF; 1=ON)	
49	Set RTTY filter notch (0=OFF; 1=ON)	
19	00	Read the transceiver ID
1A	00	Send/read memory contents
	01	Send/read band stacking register contents
	02	Send/read CW keyer contents
1B	00	Set repeater tone frequency
	01	Set tone squelch tone frequency
1C	00	Set the transceiver to receive or transmit condition (0=Rx; 1=Tx)

# 14 SPECIFICATIONS

## •General

- Frequency coverage :
  - Receive 0.030–60.000 MHz<sup>\*1, \*2</sup>
  - Transmit 1.800– 1.999<sup>\*2</sup>
  - 3.500– 3.999<sup>\*2</sup>
  - 7.000– 7.300<sup>\*2</sup>
  - 10.100–10.150<sup>\*2</sup>
  - 14.000–14.350<sup>\*2</sup>
  - 18.068–18.168<sup>\*2</sup>
  - 21.000–21.450<sup>\*2</sup>
  - 24.890–24.990<sup>\*2</sup>
  - 28.000–29.700<sup>\*2</sup>
  - 50.000–54.000<sup>\*2</sup>
- <sup>\*1</sup> Some frequency bands are not guaranteed.
- <sup>\*2</sup> Depending on version
- Mode : USB, LSB, CW, RTTY, AM, FM
- Number of memory channels : 101 (99 regular, 2 scan edges)
- Antenna connector : SO-239×2 and phono (RCA; 50 Ω)
- Temperature range : –10°C to +50°C; +14°F to +122°F
- Frequency stability : Less than ±0.5 ppm 1 min. after power on. (–10 to 50°C; +14 to +122°F)
- Frequency resolution : 1 Hz
- Power supply : 13.8 V DC ±15%
- Power consumption :
 

Transmit	Max. power	23 A
Receive	Standby	3.0 A (typ.)
	Max. audio	3.5 A (typ.)
- Dimensions : 340(W)×111(H)×285(D) mm (projections not included) 13<sup>3</sup>/<sub>8</sub>(W)×4<sup>3</sup>/<sub>8</sub>(H)×11<sup>7</sup>/<sub>32</sub>(D) in
- Weight (approx.) : 9.6 kg; 21 lb 3 oz
- ACC 1 connector : 8-pin DIN connector
- ACC 2 connector : 7-pin DIN connector
- CI-V connector : 2-conductor 3.5 (d) mm (1/8")
- Display : 5-inch (diagonal) TFT color LCD

## •Transmitter

- Output power (continuously adjustable):
  - SSB/CW/RTTY/FM 5–100 W
  - AM 5–40 W
- Modulation system :
  - SSB PSN modulation
  - AM Low power modulation
  - FM Phase modulation
- Spurious emission : 50 dB (HF bands) 60 dB (50 MHz band)
- Carrier suppression : 40 dB
- Unwanted sideband suppression : 55 dB
- ΔTX variable range : ±9.999 kHz
- Microphone connector : 8-pin connector (600 Ω)

- ELEC-KEY connector : 3-conductor 6.35(d) mm (1/4")
- KEY connector : 3-conductor 6.35(d) mm (1/4")
- SEND connector : Phono (RCA)
- ALC connector : Phono (RCA)

## •Receiver

- Receive system : Triple conversion superheterodyne system
- Intermediate frequencies:
  - 1st 64.455 MHz
  - 2nd 455 kHz
  - 3rd 36 kHz
- Sensitivity (typical) :
  - SSB, CW, RTTY 0.16 μV (1.80–29.99 MHz)<sup>\*1</sup>
  - (10 dB S/N) 0.13 μV (50.0–54.0 MHz)<sup>\*2</sup>
  - AM (10 dB S/N) 13 μV (0.5–1.799 MHz)
  - 2 μV (1.80–29.99 MHz)<sup>\*1</sup>
  - 1 μV (50.0–54.0 MHz)
  - FM (12 dB SINAD) 0.5 μV (28.0–29.99 MHz)<sup>\*1</sup>
  - 0.32 μV (50.0–54.0 MHz)<sup>\*2</sup>
- <sup>\*1</sup>Pre-amp 1 is ON, <sup>\*2</sup>Pre-amp 2 is ON
- Squelch sensitivity (Pre-amp: OFF):
  - SSB, CW, RTTY Less than 5.6 μV
  - FM Less than 1 μV
- Selectivity :
  - SSB, RTTY More than 2.4 kHz/–6 dB
  - (BW: 2.4 kHz) Less than 2.8 kHz/–60 dB
  - CW (BW: 500 Hz) More than 500 Hz/–6 dB
  - Less than 700 Hz/–60 dB
  - AM (BW: 6 kHz) More than 6.0 Hz/–6 dB
  - Less than 15.0 Hz/–60 dB
  - FM (BW: 15 kHz) More than 12.0 Hz/–6 dB
  - Less than 20.0 Hz/–60 dB
- Spurious and image rejection ratio : More than 70 dB (except IF through on 50 MHz band)
- AF output power : More than 2.0 W at 10% distortion with an 8 Ω load
- RIT variable range : ±9.999 kHz
- PHONES connector : 3-conductor 6.35 (d) mm (1/4")
- External SP connector : 2-conductor 3.5 (d) mm (1/8")/8 Ω

## •Antenna tuner

- Matching impedance range:
  - HF bands 16.7 to 150 Ω unbalanced (Less than VSWR 3:1)
  - 50 MHz band 20 to 125 Ω unbalanced (Less than VSWR 2.5:1)
- Minimum operating input power : 8 W
- Tuning accuracy : VSWR 1.5:1 or less
- Insertion loss (after tuning) : Less than 1.0 dB

All stated specifications are typical and subject to change without notice or obligation.

## IC-PW1 HF/50 MHz ALL BAND 1 kW LINEAR AMPLIFIER



Full-duty 1 kW linear amplifier including an automatic antenna tuner. Has automatic tuning and band selection capability. Full break-in (QSK) operation is possible. The amplifier/power supply unit and the remote control unit are separated.

## SM-20 DESKTOP MICROPHONE



Unidirectional, electret microphone for base station operation. Includes [UP]/[DOWN] switches and a low cut function.

## AH-4 HF/50 MHz AUTOMATIC ANTENNA TUNER



Specially designed to tune a long wire antenna for portable or mobile HF operation. The PTT tuner start function provides simple operation.

- Input power rating: 120 W

## AH-2b ANTENNA ELEMENT



A 2.5 m long antenna element for mobile operation with the AH-4.

- Frequency coverage: 3.5–28 MHz bands with the AH-4

## SP-20 EXTERNAL SPEAKER



4 audio filters; headphone jack; can connect to 2 transceivers.

- Input impedance: 8  $\Omega$
- Max. input power: 5 W

## CT-17 CI-V LEVEL CONVERTER



For remote transceiver control using a personal computer. You can change frequencies, operating mode, memory channels, etc.

## HM-36 HAND MICROPHONE

Hand microphone equipped with the [UP]/[DOWN] switches.

## UT-102 VOICE SYNTHESIZER UNIT

Announces the receive frequency, mode, S-meter level and current time in a clear, electronically-generated voice, in English (or Japanese).

## SP-21 EXTERNAL SPEAKER

Designed for base station operation.

- Input impedance: 8  $\Omega$
- Max. input power: 5 W

**Count on us!**

